



DECLARATION

I, the undersigned, of #407, Tojiji-cho 26-1, Nakagyo-ku, Kyoto, Japan, hereby certify that I am well acquainted with the English and Japanese languages, that I am an experienced translator for patent matter, and that the attached document is a true English translation of

Japanese Patent Application No. **2003-133342**

that was filed in Japanese.

I declare that all statements made herein of my own knowledge are true, that all statements made on information and belief are believed to be true, and that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code.

Signature:

A handwritten signature in black ink, appearing to read "Tomoko Tanaka".

Tomoko Tanaka

Dated: **March 5, 2007**

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

[Name of the Document] Specification

[Title of the Invention] CURRENT DRIVING DEVICE AND DISPLAY DEVICE

[Claims]

[Claim 1] A current driving device provided on a semiconductor chip, comprising:

5 a first-conductive-type first MISFET to which from a reference current source for making a reference current flow, the reference current is transmitted;

a first-conductive-type current distribution MISFET which constitutes a current mirror circuit together with the first MISFET and makes the reference current flow;

10 a second-conductive-type current input MISFET connected to the current distribution MISFET;

a plurality of current supply sections each including second-conductive-type current source MISFETs constituting a current mirror circuit together with the current input MISFET and an output terminal for outputting a current in accordance with display data;

15 a second-conductive-type current transmission MISFET constituting a current mirror circuit together with the current source MISFETs and the current input MISFET; and

a reference current output terminal which is provided on a region of the semiconductor chip located at a distance of 200 μm or less from the current transmission MISFET and outputs a current transmitted from the current transmission MISFET.

[Claim 2] The current driving device of claim 1, wherein the reference current output terminal is provided on a region of the semiconductor chip located at a distance of 100 μm or less from the current transmission MISFET.

[Claim 3] The current driving device of claim 1 or 2, wherein the reference current source is located outside of the semiconductor chip, and

wherein a first reference current input terminal which is connected to the reference current source and transmits a current to the current input MISFET is further provided on a region of the semiconductor chip located at a distance of 200 μm or less.

[Claim 4] The current driving device of claim 3, wherein the reference current
5 input terminal is provided on a region of the semiconductor chip located at a distance of 100 μm or less from the current input MISFET.

[Claim 5] The current driving device of any one of claims 1 through 4, wherein a current mirror circuit including a first-conductive-type MISFET is further provided on a transmission path through which the reference current is transmitted from the current
10 transmission MISFET to the reference current output terminal.

[Claim 6] The current driving device of claim 5, wherein a current mirror circuit including a second-conductive-type MISFET is further provided on a transmission path through which the reference current is transmitted from the reference current source to the first MISFET.

[Claim 7] The current driving device of claim 1 or 2, further comprising:
15 a first reference current input terminal connected to a drain of the first MISFET and provided on a region of the semiconductor chip located at a distance of 200 μm or less from the current input MISFET;

an input side current mirror circuit connected to the drain of the first MISFET and
20 including a second-conductive-type MISFET;

a second reference current input terminal connected to the input side current mirror circuit and provided on a region of the semiconductor chip located at a distance of 200 μm or less from the current input MISFET; and

an output side current mirror circuit provided on a current transmission path from
25 the current transmission MISFET to the reference current output terminal and including a

first-conductive-type MISFET.

[Claim 8] The current driving device of any one of claims 1 through 7, wherein a plurality of units of the current distribution MISFET and the current input MISFET are provided for the semiconductor chip.

5 [Claim 9] The current driving device of claim 8, further comprising between each of the current distribution MISFETs and each of the current input MISFETs, connection changing means for changing a connection so that each of the current distribution MISFETs is connected to a different one of current input MISFETs in every predetermined period.

10 [Claim 10] The current driving device of any one of claims 1 through 9, wherein on the semiconductor chip, a plurality of MISFET regions each collectively including the current source MISFETs are arranged in a row, and

wherein each of the plurality of current supply sections includes MISFETs arranged in at least two of the plurality of MISFET regions.

15 [Claim 11] The current driving device of claim 8, wherein respective gate electrodes of the current distribution MISFETs are connected to a bias line so as to share the bias line with one another, and

wherein a resistance element is further provided on the bias line and between gate respective electrodes of adjacent ones of the current distribution MISFETs.

20 [Claim 12] A current driving device comprising:

a first-conductive-type first MISFET in which a reference current flows in a driving state;

a first-conductive-type first current distribution MISFET which constitutes a current mirror circuit together with the first MISFET and makes the reference current flow;

25 a second-conductive-type first current input MISFET having a drain connected to

the first current distribution MISFET; and

a plurality of current supply sections each including second-conductive-type current source MISFETs constituting a current mirror circuit together with the first current input MISFET, switches which are connected to the current source MISFETs and turn ON or OFF a current flowing in the current source MISFETs in accordance with display data, and an output terminal which is connected to the switches and outputs a current in accordance with the display data to a display panel,

the current driving device being provided on a semiconductor chip,

wherein a plurality of units of the first current distribution MISFET and the first current input MISFET are provided for the semiconductor chip, and

wherein a bias line connected to a gate electrode of the first MISFET and gate electrodes of the first current distribution MISFETs and shared by the gate electrodes is further provided.

[Claim 13] The current driving device of claim 12, wherein all of respective gate electrodes of the current source MISFETs in the plurality of current supply sections and a gate electrode of the first current input MISFET are connected to one another.

[Claim 14] The current driving device of claim 12 or 13, wherein each of the plurality of current supply sections includes a second-conductive-type first cascode MISFET which is provided between each of the switches and the output terminal and is turned ON when a voltage equal to or lower than a power supply voltage of the display panel is applied to a gate electrode in a driving state.

[Claim 15] The current driving device of claim 12 or 13, wherein each of the switches is a second cascode MISFET which forms a cascode connection together with the current source MISFETs and is controlled to be turned ON or OFF depending on whether or not a predetermined voltage is applied to a gate electrode in a driving state.

[Claim 16] The current driving device of any one of claims 12 through 15, further comprising:

a first-conductive-type second MISFET which is connected to the first MISFET and in which the reference current flows in a driving state, and

5 a first-conductive-type second current distribution MISFET provided between each of the first current distribution MISFETs and each of the first current input MISFETs and having a gate electrode connected to a gate electrode of the second MISFET.

[Claim 17] The current driving device of any one of claims 12 through 16, further comprising between each of the first current distribution MISFETs and each of the first
10 current input MISFETs, connection changing means for changing a connection so that each of the first current distribution MISFETs is connected to a different one of the current input MISFETs in every arbitrary period.

[Claim 18] The current driving device of claim 17, wherein the connection changing means includes

15 a first bias current switch, and
a second bias current switch.

[Claim 19] The current driving device of claim 17 or 18, further comprising:

a first-conductive-type dummy current distribution MISFET constituting a current mirror circuit together with the first MISFET and the first current distribution MISFET;

20 and

a dummy connection changing means for temporarily connecting the dummy current distribution MISFET and the current input MISFET.

[Claim 20] The current driving device of claim 18, wherein on the semiconductor chip, further provided are

25 a first terminal temporarily connected to the first bias current changing switch in a

driving state and

a second terminal temporarily connected to the second bias current changing switch in a driving state.

[Claim 21] The current driving device of any one of claims 12 through 20, on the semiconductor chip, a plurality of MISFET regions each collectively including the current source MISFETs are arranged in a row, and

wherein each of the plurality of current supply sections includes MISFETs arranged in at least two of the MISFET regions.

[Claim 22] The current driving device of any one of claims 12 through 21, wherein on the semiconductor chip, a plurality of MISFET regions each collectively including the current source MISFETs are arranged in a row, and

wherein each of the plurality of current supply sections includes MISFETs arranged in at least two of the MISFET regions.

[Claim 23] The current driving device of any one of claims 12 through 22, further comprising:

a plurality of first-conductive-type third current distribution MISFETs for transmitting the reference current in a driving state;

a plurality of second-conductive-type second current input MISFETs each having a gate electrode connected to an associated one of respective gate electrodes of the plurality of third current distribution MISFETs and a drain connected to an associated one of respective drains of the plurality of third current distribution MISFETs; and

a second-conductive-type third cascode MISFET which constitutes a current mirror circuit together with the second current input MISFETs and is provided between the current source MISFETs and one of the switches.

[Claim 24] A current driving device comprising:

a first-conductive-type first current input MISFET in which a first reference current flows in a driving state;

a first-conductive-type second current input MISFET in which a second reference current flows in a driving state; and

5 a plurality of current supply sections each including first-conductive-type current source MISFETs constituting a current mirror circuit together with the first current input MISFET, switches which are connected to the current source MISFETs and turn ON or OFF a current flowing in the current source MISFETs in accordance with display data, a first-conductive-type cascode MISFET which is provided between the current source
10 MISFETs and one of the switches and constitutes a current mirror circuit together with the second current input MISFET, and an output terminal which is connected to the switches and outputs a current in accordance with the display data,

the current driving device being provided on a semiconductor chip.

[Claim 25] The current driving device of claim 24, wherein on the semiconductor
15 chip, further provided are

a first reference current input terminal for receiving the first reference current,

a first reference current output terminal for outputting the first reference current,

a second reference current input terminal for receiving the second reference current,

and

20 a second reference current output terminal for outputting the second reference current, and

wherein the first reference current input terminal and the first reference current output terminal are provided in parts of the semiconductor chip, respectively, so that the plurality of current supply sections are interposed between the first reference current input
25 terminal and the first reference current output terminal.

[Claim 26] A current driving device provided on a semiconductor chip, the device comprising:

a first reference current input terminal for receiving a first reference current;

a first-conductive-type first current input MISFET to which a current flowing in the
5 first reference current input terminal is transmitted in a first period;

a plurality of current supply sections each including first-conductive-type current source MISFETs constituting a current mirror circuit together with the first current input MISFET in the first period and an output terminal for outputting a current in accordance with display data;

10 a first-conductive-type first current transmission MISFET constituting a current mirror circuit together with the first current input MISFET and the current source MISFETs in the first period;

a first reference current output terminal to which a current flowing in the first current transmission MISFET is transmitted in the first period;

15 a second reference current input terminal for receiving a second reference current;

a first-conductive-type second current input MISFET to which a current flowing in the second reference current input terminal is transmitted in a second period and which constitutes a current mirror circuit together with the current source MISFETs;

a first-conductive-type second current transmission MISFET constituting a current
20 mirror circuit together with the current source MISFETs in the second period;

a second reference current output terminal to which a current flowing in the second current transmission MISFET is transmitted in the second period;

a first switch provided on a current transmission path between the first reference current input terminal and the first current input MISFET;

25 a second switch provided on a current transmission path between the first current

transmission MISFET and the first reference current output terminal;

a third switch provided on a current transmission path between the second reference current input terminal and the second current input MISFET; and

a fourth switch provided on a current transmission path between the second current transmission MISFET and the second reference current output terminal.

[Claim 27] The current driving device of claim 26, wherein the current transmission path between the first reference current input terminal and the first current input MISFET and the current transmission path between the second current transmission MISFET and the second reference current output terminal share a first shared interconnect,

wherein the current transmission path between the second reference current input terminal and the second current input MISFET and the current transmission path between the first current transmission MISFET and the first reference current output terminal share a second shared interconnect,

wherein the current driving device further includes, on the first shared interconnect, a first reference current switch for turning ON an output current of the first current input MISFET in the first period and turning ON an output current of the second current output MISFET in the second period, and

wherein the current driving device further includes, on the second shared interconnect, a second reference current switch for turning ON an output current of the first current output MISFET in the first period and turning ON an output current of the second current input MISFET in the second period.

[Claim 28] A display device comprising:

a display panel in which a pixel circuit including a light emitting element having a luminance variable in accordance with the amount of a supplied current is provided; and

a current driving device which is provided on each of a plurality of semiconductor

chips arranged in a row and supplies a driving current to the pixel circuit,

wherein each of the plurality of the semiconductor chips includes a reference current input terminal for receiving a reference current in an end portion and a reference current output terminal for outputting a reference current for a semiconductor chip in a subsequent stage in another end portion, and

wherein the reference current input terminal and the reference current output terminal located in adjacent ones of the plurality of the semiconductor chips, respectively, are provided so as to face each other.

[Claim 29] A display panel comprising:

a display panel in which a pixel circuit including a light emitting element having a luminance variable in accordance with the amount of a supplied current is provided; and

a plurality of semiconductor chips each including a current driving device for supplying a driving current to the pixel circuit,

wherein the current driving device includes

a first-conductive-type first MISFET in which a reference current flows in a driving state,

a plurality of first-conductive-type current distribution MISFETs which constitutes a current mirror circuit together with the first MISFET and makes the reference current flow,

a plurality of second-conductive-type current input MISFETs each having a drain connected to each of the plurality of the current distribution MISFETs, and

a plurality of current supply sections each including second-conductive-type current source MISFETs constituting a current mirror circuit together with the current input MISFET and an output terminal for outputting to the pixel circuit a driving current in accordance with the display data.

[Claim 30] A display device comprising:

a display panel in which a pixel circuit including a light emitting element having a luminance variable in accordance with the amount of a supplied current is provided; and

a plurality of semiconductor chips each including a current driving device for
5 supplying a driving current to the pixel circuit,

wherein the current driving device includes

a first-conductive-type first current input MISFET in which a first reference current flows in a driving state,

a first-conductive-type second current input MISFET in which a second reference
10 current flows in a driving state, and

a plurality of current supply sections each including first-conductive-type current source MISFETs constituting a current mirror circuit together with the first current input MISFET, switches which are connected to the current source MISFETs and turn ON or OFF a current flowing in the current source MISFETs in accordance with display data, a
15 first-conductive-type cascode MISFET which is provided between the current source MISFETs and the switches and constitutes a current mirror circuit together with the second current input MISFET, and an output terminal which is connected to the switches and outputs to the pixel circuit a driving current in accordance with the display data.

[Claim 31] The display device of claim 30, wherein in an end portion of each of the
20 plurality of semiconductor chips, further provided are

a first reference current input terminal for receiving the first reference current,

a first reference current output terminal for outputting the first reference current,

a second reference current input terminal for receiving the second reference current,

and

25 a second reference current output terminal for outputting the second reference

current,

wherein the first reference current output terminal is connected to the first current input terminal of an adjacent semiconductor chip, and

wherein the second reference current terminal is connected to the second reference current input terminal of the adjacent semiconductor chip.

[Detailed Description of the Invention]

[0001]

[Technical Field to which the Invention Belongs]

The present invention relates to current driving devices, and more particularly relates to a technique used for a preferable current driving device as a display driver such as an organic EL (electro luminescence) panel.

[0002]

[Prior Art]

In recent years, the size and definition of flat panel displays such as organic EL panels have been increased. At the same time, flat panel displays have been made thinner and lighter and also costs for fabricating such panels have been reduced. In general, an active matrix method is preferably used as a driving method for a large-size, high definition display panel. Hereinafter, a known display driver for an active matrix display panel will be described.

[0003]

FIG. 20 is a circuit diagram illustrating the configurations of a display panel and a known current driving device serving as a display driver connected to the display panel. Herein, a display panel means to be an organic EL panel.

[0004]

As shown in FIG. 20, the known current driving device includes current supply

sections **1001a1**, **1001a2**, ... and **1001an** (hereinafter, referred to as a “current supply section **1001a** when the current supply sections are not distinguished from each other) for supplying driving currents to a plurality of pixel circuits **1005a1**, **1005a2**, ... and **1005an** (hereinafter, referred to as a “pixel circuit **1005a** when the pixel circuits are not distinguished from each other) formed on a display panel, respectively, and a reference current supply section (bias circuit) **1101** for supplying a reference current to each section in the current supply section **1001a**. Note that a “reference current” herein means to be not only a predetermined current flowing from a reference current generator but also a current from a reference current generator transmitted by a current mirror circuit.

[0005]

When the size of a display panel is large as in a television display device, a large number of current supply sections **1001a** are provided so that the current supply sections **1001a** are divided onto a plurality of semiconductor chips **1105**. The semiconductor chips **1105** are arranged in a frame portion of a display panel in many cases.

[0006]

Each of the pixel circuits **1005a1**, **1005a2**, ... and **1005an** includes a p-channel first TFT (thin-film-transistor) **1104** connected to the current supply section **1001a** via a signal line, a second TFT **1102** constituting a current mirror circuit together with the first TFT **1104**, and an organic EL device **1103** for emitting light in accordance with a current supplied from the second TFT **1102**.

[0007]

The reference current supply section **1101** includes a p-channel first MISFET **1108** to which a supply voltage is supplied at a terminal, a resistor **1107** which is connected with the first MISFET **1108** and generates a reference current, a p-channel second MISFET **1109** constituting a current mirror circuit together with the first MISFET **1108**, and an n-

channel current input MISFET **1110** for transmitting a reference current to the current supply portion **1001a**.

[0008]

When a gray scale of m bits is controlled, each of the current supply section **1001a** includes current sources **1112-1**, **1112-2**, ... and **1112- m** (m is a positive integer) arranged in parallel to an output section connected to the pixel circuit **1005a** and switches **1115-1**, **1115-2**, ... and **1115- m** for controlling currents flowing in the current sources **1112-1**, **1112-2**, ... and **1112- m** , respectively, to turn the current ON or OFF. Herein, each of the current sources **1112-1**, **1112-2**, ... and **1112- m** is formed of an n-channel MISFET **1110** constituting a current mirror circuit together with the current input MISFET **1110**. Moreover, each of the switches **1115-1**, **1115-2**, ... and **1115- m** independently performs a switching operation based on display data.

[0009]

FIG. **23** is a circuit diagram illustrating the arrangement and configuration of a current supply section in the known current driving device. In FIG. **23**, an example of current supply sections for 64 gray scale in which six current sources are provided in each current supply section is shown. The current sources **1112-1**, **1112-2**, ... and **1112- m** include an MISFET, two MISFETs, ... and 32 MISFETs having the same size and properties, respectively. These MISFETs are arranged in the manner shown in the upper part of FIG. **23** when viewed from the top. Connections are made so that adjacent ones of the MISFETs are connected to a single output section.

[0010]

With the above-described configuration, the current supply section **1001a** is substantially operated as a current mode D/A converter, receives display data as a digital signal, and withdraws as an analog signal a current having an amount corresponding to the

display data from an output section.

[0011]

As has been known, an organic EL device has the rectifying action as a diode does and the illuminance of the organic EL device varies in accordance with the amount of a current conducted. In the pixel circuit **1005a**, the amount of a current conducted by the organic EL device **1103** varies in accordance with the amount of a current flowing in the TFT **1104**. Accordingly, the organic EL device **1103** is current-driven by the current supply section **1001a**, so that the illuminance of the organic EL device **1103** varies.

[0012]

As has been described, the current driving device current-drives the plurality of pixel circuits **1005a** in the display panel based on display data to achieve a gray scale display (see, e.g., Japanese Unexamined Patent Publication No. 11-88072 and Japanese Unexamined Patent Publication No. 11-340765).

[0013]

[Patent Reference 1]

Japanese Laid-Open Publication No. 2000-276108

[0014]

[Problems that the Invention is to solve]

However, in a display device having the above-described configuration, display distortion such as nonuniformity sometimes occurs while an image is displayed. There seem to be several possible reasons for this.

[0015]

First, display distortion due to charge injection from the display panel and momentary change of a bias voltage, i.e., the generation of so-called “crosstalk” is considered to be a possible reason. Hereinafter, description on this “crosstalk” will be

given.

[0016]

FIG. **21(a)** is a view illustrating an example of black and white displays in a display panel. FIG. **21(b)** is a circuit diagram illustrating the pixel circuits arranged along the line
5 XXIIb-XXIIb of the display panel shown in FIG. **21(a)** and known current supply sections connected to the pixel circuits. FIG. **21(c)** is a graph showing an operating point of a TFT in a black display state. And FIG. **21(d)** is a graph showing an operating point of the TFT in a white display state. Moreover, FIG. **22(a)** is a view illustrating an example of black and white displays in a display panel, as FIG. **21(a)**. FIG. **22(b)** is a circuit diagram
10 illustrating the pixel circuits arranged along the line XXIIb-XXIIb of the display panel shown in FIG. **22(a)** and known current supply sections connected to the pixel circuits. FIG. **22(c)** is a graph showing an operating point of a TFT when a black display is changed to a white display. And FIG. **22(d)** is a graph showing an operating point of the TFT when a white display is continuously performed.

[0017]

As shown in FIG. **21(b)**, when the known display device performs a black display, all of the switches **1115-1**, **1115-2**, ... and **1115-m** in the current supply section **1001a** are in an OFF state. When the known display device performs a white display, all of the switches **1115-1**, **1115-2**, ... and **1115-m** in the current supply section **1001a** are in ON
20 state.

[0018]

At this time, a stray capacitance **1220a1** generated in the pixel circuit **1005a1** for performing a black display and a signal line connected to the pixel circuit **1005a1** and the like are charged by a power supply, so that each of gate voltages of the first and second
25 TFTs **1104** and **1102** is increased to, for example, about 4 V. As shown in FIG. **21(c)**, an

operating point of the first and second TFTs **1104** and **1102** at this time is an intersection of the IV characteristic curve of the current supply section **1001a** and the IV characteristic curve of a TFT.

[0019]

5 On the other hand, when a white display is performed, charge is drawn to the current supply section **1001an** side, so that charge stored in a stray capacitance **1220an** generated in the pixel circuit **1005an** and a signal line connected to the pixel circuit **1005an** is less than that when a black display is performed. Accordingly, each of gate voltages of the first and second TFTs **1104** and **1102** becomes, for example, about 2 V and
10 an operating point of the first and second TFTs **1104** and **1102** is lower than in the case of a black display. These operating points are varied due to an ON resistance of a TFT and the amount of current withdrawn by the current supply section **1001a**.

[0020]

Moreover, in FIG. **22(b)**, the pixel circuit and the current supply section when a black
15 display is changed to a white display, and the pixel circuit and the current supply section when a white display is continuously performed are shown. When a black display is changed to a white display, all of the switches **1115-1**, **1115-2**, ... and **1115-6** of the current supply section **1001a1** are turned ON and then a current at a maximum amount flows from the panel side. Thus, the organic EL device **1103** in the pixel circuit **1005a1** emits light at
20 a maximum illuminance.

[0021]

At this time, the charge stored in the stray capacitance **1220a1** is injected to the current supply section **1001a1** via the signal line.

[0022]

25 When the amount of charge injected is relatively small, the charge passes through

the current sources **1112-1**, **1112-2**, ... and **1112-6** to reach the ground. However, since the pixel circuit **1005a1** performed a black display until immediately before a white display is initiated, the stray capacitance **1220a1** is charged to a level close to the power supply voltage. Accordingly, at the moment when the current supply section **1001a1** and the pixel circuit **1005a1** are electrically connected to each other, a voltage close to the power supply voltage is applied to the drain of each of the current sources **1112-1**, **1112-2**, ... and **1112-6**, so that the potential of a bias line **1050** is temporarily increased via a parasitic capacitance **C_{gd}** which exists between a gate and a drain. The waveform **1051** shown in FIG. **22(b)** shows change in a voltage generated in the bias line **1050**.

[0023]

A gate electrode of a current source in another current supply section **1001a** is connected to a bias line **1050**. Thus, when voltage change as indicated by the waveform **1051** occurs in the bias line **1050**, the amount of a current flowing in the current supply section **1001a** is temporarily increased. As a result, the current supply section **1001a** is temporarily in an excessive driving state, as shown by a dotted line in FIG. **22(d)**.

[0024]

If change in the voltage of the bias line **1050** converges during a display data writing period, the current supply section **1001a** is back to a predetermined driving state, so that a normal display is performed. However, if change in the voltage of the bias line **1050** does not converge during a display data writing period, the pixel circuit **1005a** is continuously in the excessive driving state also in a subsequent frame. Thus, a crosstalk display in which a luminescent line is visually recognized is generated.

[0025]

However, by contrast to the above-described case, a temporary drop of a voltage occurs in the bias line **1050** when a white display is changed to a black display. Thus, a

crosstalk in which a dark line with reduced luminance is visually recognized is generated.

[0026]

By the way, the stray capacitance **1220a** is several pF to several tens pF in a small panel used for cellular phones. There are also large panels in which the stray capacitance
5 **1220a** is 100 pF or more. As the size of a display panel becomes larger, such a crosstalk display appears more clearly. Specifically, the current driving device for an organic EL panel drives a pixel circuit by a very small current of about several tens A. Thus, a crosstalk display is easily generated.

[0027]

10 Note that there may be cases in which some other factor causes distortion of an image display than the above-described crosstalk.

[0028]

Moreover, in recent years, display panel screens become larger and larger. With the increase in the display panel size, there are cases in which the length of a display
15 device driver LSI (i.e., the length in the direction in which a longer side thereof extends) is 10-20 mm. In this case, if a semiconductor chip including the known current driving device is used, output voltages vary between output terminals separately located from each other. This might cause reduction in image quality such as the generation of a shading portion in a display image.

20 [0029]

The present inventors examined factors causing variations in output voltage between the output terminals of the display device driver LSI (semiconductor chip) and then found that currents distributed to MISFETs constituting the current source **1112** (see FIG. 20) located on the semiconductor chip varied. In the first place, the current mirror
25 circuit is provided on the assumption that diffusion conditions for transistors constituting

the current mirror circuit are the same and thus there is no significant difference in threshold voltage V_t and carrier mobility. Then, according to the ratio between the transistor sizes, currents are distributed. However, if the length of a chip of the display device driver LSI is 10-20 mm, it seems difficult to uniformly diffuse an impurity
5 contained in each of the transistors. In addition, if the transistors are located in a different manner, variation in display may be generated due to variations in fabrication process steps such as etching. As a result, the threshold of a transistor to serve as a current mirror varies. If the threshold varies, application of the same gate voltage causes an error for an output current. Normally, the diffusion change shows gradual increase or decrease in a wafer
10 surface. Thus, even when a uniform display based on a constant display data is performed, a gradation from bright to dark is generated on the display panel.

[0030]

Moreover, in the display device including a large screen display panel, a plurality of semiconductor chips in which a current driving device including a current supply
15 section is provided are used. In this case, values for currents output from the respective current driving devices located on different semiconductor chips vary. In the display device, fabrication conditions such as diffusion conditions for the semiconductor chips arranged adjacent to each other are different in many cases. Accordingly, properties of MISFETs constituting a current source of the current supply section **1001a1** widely vary.
20 Therefore, display nonuniformity is visibly recognized in each of the semiconductor chips in more cases.

[0031]

Thus, variation in each output section of the current supply section **1001a** and also variation in properties of each of the semiconductor chips cause distortion in a display
25 image as in the same manner as a crollstalk.

[0032]

It is therefore an object of the present invention to solve any one of the various problems described above, thereby providing a current driving device which allows suppression of distortion in an image display.

5 [0033]

[Means for Solving the problems]

A first current driving device according to the present invention is a current driving device provided on a semiconductor chip, including: a first-conductive-type first MISFET to which from a reference current source for making a reference current flow, the reference current is transmitted; a first-conductive-type current distribution MISFET which constitutes a current mirror circuit together with the first MISFET and makes the reference current flow; a second-conductive-type current input MISFET connected to the current distribution MISFET; a plurality of current supply sections each including second-conductive-type current source MISFETs constituting a current mirror circuit together with the current input MISFET and an output terminal for outputting a current in accordance with display data; a second-conductive-type current transmission MISFET constituting a current mirror circuit together with the current source MISFETs and the current input MISFET; and a reference current output terminal which is provided on a region of the semiconductor chip located at a distance of 200 μm or less from the current transmission MISFET and outputs a current transmitted from the current transmission MISFET.

[0034]

Thus, when a plurality of semiconductor chips each including the current driving device of the present invention are arranged and a large screen display panel is driven, a current with a small error can be transmitted to a semiconductor chip in a subsequent stage. Therefore, variation in output currents in each semiconductor chip can be reduced,

compared to a known current driving circuit. As a result, a large screen or high definition display device in which display nonuniformity and display distortion are suppressed can be achieved.

[0035]

5 It is more preferable that the reference current output terminal is provided on a region of the semiconductor chip located at a distance of 100 μm or less from the current transmission MISFET, because an error of a current transmitted to a semiconductor chip in a subsequent stage can be further reduced.

[0036]

10 If the reference current source is located outside of the semiconductor chip, and a first reference current input terminal which is connected to the reference current source and transmits a current to the current input MISFET is further provided on a region of the semiconductor chip located at a distance of 200 μm or less, a reference current output from a semiconductor chip in a previous stage can be transmitted to a current input MISFET
15 with a small error in the case where semiconductor chips are cascaded. Therefore, when the first current driving device is used for a display device, display nonuniformity in each semiconductor chip can be reduced.

[0037]

If the current driving device further includes: a first reference current input terminal
20 connected to a drain of the first MISFET and provided on a region of the semiconductor chip located at a distance of 200 μm or less from the current input MISFET; an input side current mirror circuit connected to the drain of the first MISFET and including a second-conductive-type MISFET; a second reference current input terminal connected to the input side current mirror circuit and provided on a region of the semiconductor chip located at a
25 distance of 200 μm or less from the current input MISFET; and an output side current

mirror circuit provided on a current transmission path from the current transmission MISFET to the reference current output terminal and including a first-conductive-type MISFET, pixel circuits on a display panel can be driven with semiconductor chips of a single type arranged. Therefore, fabrication costs for a display device can be reduced,
5 compared to the case where semiconductor chips of different types are used.

[0038]

When a plurality of units of the current distribution MISFET and the current input MISFET are provided for the semiconductor chip, the number of gate electrodes of current source MISFETs connected to a current input MISFET can be reduced, compared to the
10 known device. Accordingly, change in the gate potential of current source MISFETs can rapidly converge. Therefore, with the current driving device of the present invention, display nonuniformity in each semiconductor chip can be suppressed while the generation of a crosstalk can be suppressed.

[0039]

15 When the current driving device of the present invention further includes between each of the current distribution MISFETs and each of the current input MISFETs, connection changing means for changing a connection so that each of the current distribution MISFETs is connected to a different one of current input MISFETs in every predetermined period, property variation of the current distribution MISFET can be
20 averaged. Therefore, a display device in which display nonuniformity is further suppressed can be achieved.

[0040]

If on the semiconductor chip, a plurality of MISFET regions each collectively including the current source MISFETs are arranged in a row, and each of the plurality of
25 current supply sections includes MISFETs arranged in at least two of the plurality of

MISFET regions, property variation of the current source MISFETs can be averaged. Therefore, a display device of which display nonuniformity is hardly recognized visually and which has high display quality can be achieved.

[0041]

5 If respective gate electrodes of the current distribution MISFETs are connected to a bias line so as to share the bias line with one another, and a resistance element is further provided on the bias line and between respective gate electrodes of adjacent ones of the current distribution MISFETs, a gate voltage applied to the current distribution MISFET can be changed in accordance with variation in the threshold of the current distribution
10 MISFET. As a result, variation in a reference current distributed to each of the current supply sections can be reduced.

[0042]

A second current driving device according to the present invention includes: a first-conductive-type first MISFET in which a reference current flows in a driving state; a first-
15 conductive-type first current distribution MISFET which constitutes a current mirror circuit together with the first MISFET and makes the reference current flow; a second-conductive-type first current input MISFET having a drain connected to the first current distribution MISFET; and a plurality of current supply sections each including second-conductive-type current source MISFETs constituting a current mirror circuit together with
20 the first current input MISFET, switches which are connected to the current source MISFETs and turn ON or OFF a current flowing in the current source MISFETs in accordance with display data, and an output terminal which is connected to the switches and outputs a current in accordance with the display data to a display panel, the current driving device being provided on a semiconductor chip. In the current driving device, a
25 plurality of units of the first current distribution MISFET and the first current input

MISFET are provided for the semiconductor chip, and a bias line connected to a gate electrode of the first MISFET and gate electrodes of the first current distribution MISFETs and shared by the gate electrodes is further provided.

[0043]

5 Thus, the number of gate electrodes of the current source MISFETs connected to the first current input MISFET can be reduced, compared to the known device, so that change in a gate potential of the current source MISFETs can be rapidly converges. Accordingly, with the current driving device of the present invention, the generation of a crosstalk display can be suppressed. Therefore, a display device including a large screen
10 or high definition display panel can be achieved.

[0044]

 If all of respective gate electrodes of the current source MISFETs in the plurality of current supply sections and a gate electrode of the first current input MISFET are connected to one another, a gate potential applied to the current source MISFETs can be
15 changed in accordance with variation of the threshold. Therefore, variation in output currents in each output terminal can be suppressed.

[0045]

 If each of the plurality of current supply sections includes a second-conductive-type first cascode MISFET which is provided between each of the switches and the output
20 terminal and is turned ON when a voltage equal to or lower than a power supply voltage of the display panel is applied to a gate electrode in a driving state, application of a high voltage from the display panel to the current source MISFETs can be prevented in changing a display in the case where the current driving device of the present invention is used and the first cascode MISFET is the n-channel type. Therefore, the generation of a
25 crosstalk display can be suppressed.

[0046]

Also, if each of the switches is a second cascode MISFET which forms a cascode connection together with the current source MISFETs and is controlled to be turned ON or OFF depending on whether or not a predetermined voltage is applied to a gate electrode in a driving state, the second cascode MISFET can limit a high voltage applied from the display panel in the case where output terminals are connected to the display panel. More specifically, if each of the switches is made to serve as a current limiting MISFET, a circuit area can be reduced, compared to the case where a voltage limiting MISFET is separately provided.

[0047]

If the second current driving device further includes between each of the first current distribution MISFETs and each of the first current input MISFETs, connection changing means for changing a connection so that each of the first current distribution MISFETs is connected to a different one of the current input MISFETs in every arbitrary period, reference currents distributed by the current distribution MISFET are shuffled and output. Therefore, property variation of the current distribution MISFET can be averaged.

[0048]

More specifically, it is preferable that the connection changing means includes a first bias current switch and a second bias current switch.

[0049]

If on the semiconductor chip, further provided are a first terminal temporarily connected to the first bias current changing switch in a driving state and a second terminal temporarily connected to the second bias current changing switch in a driving state, change can be made so that currents distributed by the current distribution MISFETs are output from the output terminal of an adjacent semiconductor chip via the first terminal and

second terminal. Thus, variation in output currents in a semiconductor chip but also variation in output currents in adjacent semiconductor chips can be averaged.

[0050]

Moreover, if the second current driving device of the present invention further
5 includes: a first-conductive-type dummy current distribution MISFET constituting a
current mirror circuit together with the first MISFET and the first current distribution
MISFET; and a dummy connection changing means for temporarily connecting the
dummy current distribution MISFET and the current input MISFET, control can be
performed so that current distribution MISFETs to be connected, for example, between
10 adjacent current input MISFETs are sequentially changed. Therefore, output currents from
output terminals can be made uniform in a relatively simple manner.

[0051]

If on the semiconductor chip, a plurality of MISFET regions each collectively
including the current source MISFETs are arranged in a row, and each of the plurality of
15 current supply sections includes MISFETs arranged in at least two of the MISFET regions,
property variations of the current distribution MISFETs and the current source MISFETs
can be averaged, so that an error of an output current between output terminals can be
reduced. More specifically, there is no need for providing another element and an
interconnect structure can be arbitrarily change. Therefore, increase in a circuit area can be
20 suppressed.

[0052]

If the second current driving device further includes a resistance element provided
on the bias line and between respective gate electrodes of adjacent ones of the current
distribution MISFETs, a gate voltage applied to the current distribution MISFETs can be
25 changed in accordance with variation of the threshold of the current distribution MISFETs.

[0053]

A third current driving device according to the present invention includes: a first-conductive-type first current input MISFET in which a first reference current flows in a driving state; a first-conductive-type second current input MISFET in which a second reference current flows in a driving state; and a plurality of current supply sections each including first-conductive-type current source MISFETs constituting a current mirror circuit together with the first current input MISFET, switches which are connected to the current source MISFETs and turn ON or OFF a current flowing in the current source MISFETs in accordance with display data, a first-conductive-type cascode MISFET which is provided between the current source MISFETs and one of the switches and constitutes a current mirror circuit together with the second current input MISFET, and an output terminal which is connected to the switches and outputs a current in accordance with the display data, the current driving device being provided on a semiconductor chip.

[0054]

Thus, an output current from an output terminal is an averaged value of a current to flow in the current source MISFETs and a current to flow in the cascode MISFET. Therefore, property variation of the current source MISFETs and property variation of the cascode MISFET can be cancelled off each other. As a result, variation in output currents from output terminals can be reduced.

[0055]

A fourth current driving device of the present invention includes: a first reference current input terminal for receiving a first reference current; a first-conductive-type first current input MISFET to which a current flowing in the first reference current input terminal is transmitted in a first period; a plurality of current supply sections each including first-conductive-type current source MISFETs constituting a current mirror

circuit together with the first current input MISFET in the first period and an output terminal for outputting a current in accordance with display data; a first-conductive-type first current transmission MISFET constituting a current mirror circuit together with the first current input MISFET and the current source MISFETs in the first period; a first
5 reference current output terminal to which a current flowing in the first current transmission MISFET is transmitted in the first period; a second reference current input terminal for receiving a second reference current; a first-conductive-type second current input MISFET to which a current flowing in the second reference current input terminal is transmitted in a second period and which constitutes a current mirror circuit together with
10 the current source MISFETs; a first-conductive-type second current transmission MISFET constituting a current mirror circuit together with the current source MISFETs in the second period; a second reference current output terminal to which a current flowing in the second current transmission MISFET is transmitted in the second period; a first switch provided on a current transmission path between the first reference current input terminal
15 and the first current input MISFET; a second switch provided on a current transmission path between the first current transmission MISFET and the first reference current output terminal; a third switch provided on a current transmission path between the second reference current input terminal and the second current input MISFET; and a fourth switch provided on a current transmission path between the second current transmission MISFET
20 and the second reference current output terminal.

[0056]

Thus, the first and second switches are turned ON in the first period and the third and fourth switches are turned OFF in the second period, so that a driving state of driving with a first reference current and a driving state of driving with a second reference current
25 can be changed around. As a result, variation in output currents from the current supply

section can be suppressed, thereby allowing a uniform display.

[0057]

A first display device according to the present invention includes: a display panel in which a pixel circuit including a light emitting element having a luminance variable in accordance with the amount of a supplied current is provided; and a current driving device which is provided on each of a plurality of semiconductor chips arranged in a row and supplies a driving current to the pixel circuit. In the first display device, each of the plurality of the semiconductor chips includes a reference current input terminal for receiving a reference current in an end portion and a reference current output terminal for outputting a reference current for a semiconductor chip in a subsequent stage in another end portion, and the reference current input terminal and the reference current output terminal located in adjacent ones of the plurality of the semiconductor chips, respectively, are provided so as to face each other.

[0058]

Thus, a transmission path through which a reference current flows can be made the shortest between semiconductor chips each including a current driving device. Therefore, variation in output currents in each semiconductor chip can be reduced, compared to the known device.

[0059]

A second display device according to the present invention includes: a display panel in which a pixel circuit including a light emitting element having a luminance variable in accordance with the amount of a supplied current is provided; and a plurality of semiconductor chips each including a current driving device for supplying a driving current to the pixel circuit. In the second display device, the current driving device includes a first-conductive-type first MISFET in which a reference current flows in a

driving state, a plurality of first-conductive-type current distribution MISFETs which constitutes a current mirror circuit together with the first MISFET and makes the reference current flow, a plurality of second-conductive-type current input MISFETs each having a drain connected to each of the plurality of the current distribution MISFETs, and a
5 plurality of current supply sections each including second-conductive-type current source MISFETs constituting a current mirror circuit together with the current input MISFET and an output terminal for outputting to the pixel circuit a driving current in accordance with the display data.

[0060]

10 Thus, change in the gate potential of the current source MISFETs can rapidly converge, so that the generation of a crosstalk display can be suppressed. Therefore, a uniform display can be achieved.

[0061]

A third display device according to the present invention includes: a display panel
15 in which a pixel circuit including a light emitting element having a luminance variable in accordance with the amount of a supplied current is provided; and a plurality of semiconductor chips each including a current driving device for supplying a driving current to the pixel circuit. In the third display device, the current driving device includes a first-conductive-type first current input MISFET in which a first reference current flows
20 in a driving state, a first-conductive-type second current input MISFET in which a second reference current flows in a driving state, and a plurality of current supply sections each including first-conductive-type current source MISFETs constituting a current mirror circuit together with the first current input MISFET, switches which are connected to the current source MISFETs and turn ON or OFF a current flowing in the current source
25 MISFETs in accordance with display data, a first-conductive-type cascode MISFET which

is provided between the current source MISFETs and the switches and constitutes a current mirror circuit together with the second current input MISFET, and an output terminal which is connected to the switches and outputs to the pixel circuit a driving current in accordance with the display data.

5 [0062]

Thus, an output current from an output terminal is an averaged value of a current to flow in the current source MISFETs and a current to flow in the cascode MISFET. Therefore, property variation of the current source MISFETs and property variation of the cascode MISFET can be cancelled off each other. As a result, variation in output currents
10 from output terminals can be reduced.

[0063]

If on each of the plurality of semiconductor chips, further provided are a first reference current input terminal for receiving the first reference current, a first reference current output terminal for outputting the first reference current, a second reference current
15 input terminal for receiving the second reference current, and a second reference current output terminal for outputting the second reference current, and the first reference current output terminal is connected to the first reference current input terminal of an adjacent semiconductor chip, and the second reference current output terminal is connected to the second reference current input terminal of the adjacent semiconductor chip, variation in
20 output currents from terminals in a single semiconductor chip can be reduced, and at the same time, variation in output currents between semiconductor chips can be reduced. Therefore, a uniform display can be performed throughout a display panel.

[0064]

[Embodiments of the Invention]

25 (First Embodiments)

FIG. 1 is a circuit diagram illustrating a connection portion of two chips each including a current driving device according to a first embodiment of the present invention.

[0065]

A display device according to this embodiment includes a display panel in which pixel circuits (not shown) each including an organic EL device is provided and a current driving device for supplying a driving current to the pixel circuit via a signal line. The current driving device is used as a source driver of a current driving type display device such as an organic EL display device, as in the current driving device shown in FIG. 20. In the display device of this embodiment, a plurality of semiconductor chips each including an integrated current driving device is provided are arranged in a frame portion of a display panel. In FIG. 1, two semiconductor chips located adjacent to each other are shown as first and second semiconductor chips 20 and 22.

[0066]

In the display device of this embodiment, the first semiconductor chip 20 includes a current supply section 40 for supplying a driving current to each of the plurality of circuits (not shown) provided in a display panel, a reference current supply section for supplying a reference current to the current supply section 40, an n-channel first current transmission MISFET 7, and a reference current output terminal 9 connected to the first current transmission MISFET 7. The reference current output terminal 9 is provided in part of the first semiconductor chip 20 facing the second semiconductor chip 22. Although the current supply section 40 is actually provided in a plural number (e.g., 528), only one current supply section 40 is shown in FIG. 1.

[0067]

The reference current supply section includes a p-channel first MISFET 1 in which a power supply voltage is supplied at one end, a reference current source 4 which is

connected to the first MISFET 1 and generates a reference current, a p-channel second MISFET (current distribution MISFET) 2 constituting a current mirror circuit together with the first MISFET 1, and an n-channel current input MISFET 3 which is connected to the second MISFET 2 and transmits a reference current to the current supply section 40.

5 [0068]

Moreover, the current supply section 40 includes current sources 5-1, 5-2, ... and 5-m (m is a positive integer) and switches for turning a current flowing each of the current sources ON or OFF. Each of the current sources 5-1, 5-2, ... and 5-m is formed of an MISFET (current source MISFET) constituting a current mirror circuit together with the
10 current input MISFET 3 and the first current transmission MISFET 7. For example, the current source 5-1 is formed of an MISFET, the current source 5-2 is formed of two MISFETs connected in parallel to one another, and the current source 5-m is formed of 2^{m-1} MISFETs connected to in parallel one another. The current supply section 40 is a so-called current mode D/A converter in which each of the switches is turned ON or OFF in
15 accordance with display data, thereby allowing 2^m gray scale display.

[0069]

In the second semiconductor chip 22, provided are a reference current input terminal 11 connected to the reference current output terminal 9, a p-channel third MISFET 13 connected to the reference current input terminal 11, a p-channel fourth
20 MISFET 15 which is cascoded to the third MISFET 13 and has a gate electrode connected to the reference current input terminal 11, a p-channel fifth MISFET 17 constituting a current mirror circuit together with the third MISFET 13, a p-channel sixth MISFET 19 which is cascoded to the fifth MISFET 17 and constitutes a current mirror circuit together with the fourth MISFET 15, an n-channel seventh MISFET 23 (corresponding to the
25 current input MISFET in the first semiconductor chip 20) for receiving a reference current

flowing in the sixth MISFET **19**, a current supply section **41** for supplying a driving current to each of the plurality pixel circuits (not shown) provided in the display panel, and an n-channel second current transmission MISFET **27** for transmitting a reference current to a semiconductor chip in a subsequent stage. Moreover, a reference current output terminal (not shown) connected to the second current transmission MISFET **27** is provided on the second semiconductor chip **22**.

[0070]

The reference current input terminal **11** is provided in the vicinity of part of the second semiconductor chip **22** facing the first semiconductor chip. More specifically, the reference current input terminal **11** is located so as to be close to the reference current output terminal **9**.

[0071]

Moreover, in the second semiconductor chip **22**, the third MISFET **13**, the fourth MISFET **15**, the fifth MISFET **17**, the sixth MISFET **19**, and the seventh MISFET **23** function as a reference current supply section for transmitting a reference current from the first semiconductor chip **20** to the current supply section **41** via the reference current output terminal **9**.

[0072]

The current supply section **41** includes current sources **25-1**, **25-2**, ... and **25-m** (m is a positive integer) and switches for turning a current flowing each of the current sources ON or OFF. Each of the current sources **25-1**, **25-2**, ... and **25-m** is formed of one or more MISFETs constituting a current mirror circuit together with the seventh MISFET **23** and the second current transmission MISFET **27**, as the current sources **5-1**, **5-2**, ... and **5-m**.

[0073]

In FIG. 1, only two semiconductor chips are shown. However, some more chip(s)

having the same configuration as that of the second semiconductor chip **22** may be further placed according to the size of the display panel. In many cases, semiconductor chips each including a current supply section are arranged in a row in a normal display device. In such a case, a reference current is transmitted from the reference current output terminal **9** provided in the vicinity of an end of each semiconductor chip to the reference current input terminal **11** in a cascade manner.

[0074]

The semiconductor chips of this embodiment having the respective configurations described above are characterized in that the reference current supply section of the second semiconductor chip **22** is placed in the vicinity of the reference current input terminal **11** and the current transmission MISFET **7** of the first semiconductor chip **20** is placed in the vicinity of the reference current output terminal **9**. In this case, each of the distance between the reference current supply section including the seventh MISFET **23** and the reference current input terminal **11** and the distance between the current transmission MISFET **7** and the reference current output terminal **9** may be a distance which does not cause variation in electric properties due to diffusion of an impurity and the like to be a problem. Although an appropriate distance differs according to fabrication conditions and process steps, a distance of 200 μm or less is permissible, and, more specifically, a distance of 100 μm or less is preferable in general.

[0075]

Therefore, an output current of the current transmission MISFET **7** of adjacent semiconductor chips can be distributed as a reference current for the second semiconductor chip **22**. Thus, variation in respective output currents of semiconductor chips (driving currents of pixel circuits) can be reduced, compared to the known device. As a result, a display device for performing a more uniform display can be achieved.

[0076]

In addition to this, in the display device of this embodiment, the reference current supply section and reference current input terminal **11** of a semiconductor chip are placed in the vicinity of part of the semiconductor chip facing a semiconductor chip in a previous stage and the current transmission MISFET and the reference current output terminal **9** are placed in the vicinity of part of the semiconductor chip facing a semiconductor chip in a subsequent stage.

[0077]

Therefore, the distance between the reference current output terminal **9** and the reference current input terminal **11** is short. Thus, variation in currents output from the current supply section between semiconductor chips can be further suppressed. However, this effect of suppressing variation between semiconductor chips is lower than that obtained by providing reference current input/output terminals in the vicinity of an MISFET for transmitting a reference current. Therefore, the reference current output terminal **9** and the reference current input terminal **11** are not necessarily provided in one end of a semiconductor chip.

[0078]

Note that in a semiconductor chip, property variation according to the location of a current supply section is smaller when the reference current supply section (or MISFET) is placed in a central portion of a chip than that when the reference current supply section is placed in one end of the chip. Accordingly, in this method, it is preferable that the reference current output terminal **9** and the reference current input terminal **11** are provided so as to be close to each other in the reference current supply section.

[0079]

As has been described, with the semiconductor chips of this embodiment, property

variation between the semiconductor chips can be suppressed. Therefore, a display device in which the generation of display distortion or the like is reduced can be achieved.

[0080]

Note that a current mirror circuit formed of a p-channel MISFET may be provided
5 between the first current transmission MISFET 7 and the reference current output terminal 9.

[0081]

FIG. 2 is a circuit diagram illustrating a connection portion of two chips each including an example of the current driving device according to the first embodiment.

10 [0082]

In the exemplary current driving device of FIG. 2, a p-channel third current transmission MISFET 10 connected to the first current transmission MISFET 7 and a p-channel fourth current transmission MISFET 12 constituting a current mirror circuit together with the third current transmission MISFET 10 are provided between the first
15 current transmission MISFET 7 and the reference current output terminal 9 in the first semiconductor chip 20.

[0083]

Moreover, the reference current supply section of the second semiconductor chip 22 has a configuration obtained by changing the conductive type of each of the MISFETs
20 constituting the reference supplying section of FIG. 1 to the other conductive type. Specifically, in the second semiconductor chip 22, provided are an n-channel eighth MISFET 33 connected to the reference current input terminal 11, an n-channel ninth MISFET 35 which is cascoded to the eighth MISFET 33 and has a gate electrode connected to the reference current input terminal 11, an n-channel tenth MISFET 37
25 constituting a current mirror circuit together with the eighth MISFET 33, an n-channel

eleventh MISFET 39 which is cascoded to the tenth MISFET 37 and constitutes a current mirror circuit together with the ninth MISFET 35, and a p-channel twelfth MISFET 43 for receiving a reference current flowing in the tenth MISFET 37. In this configuration, the distance between the reference current output terminal 9 of the first semiconductor chip 20 and each of the first current transmission MISFET 7, the third current transmission MISFET 10 and the fourth current transmission MISFET 12 is 200 μm or less. Also, each of the distance between the first current transmission MISFET 7 and the third current transmission MISFET 10 and the distance between the third current transmission MISFET 10 and the fourth current transmission MISFET 12 is 200 μm or less. Moreover, the distance between the reference current input terminal 11 and each of the eighth MISFET 33, the ninth MISFET 35, the tenth MISFET 37, the eleventh MISFET 39 and the twelfth MISFET 43 is 200 μm or less and the respective distances between the MISFETs are also 200 μm or less. In addition to this, the arrangement of the reference current input terminal 11 of the second semiconductor chip 22 and the reference current output terminal 9 of the first semiconductor chip 20 is not changed, i.e., the reference current input terminal 11 of the second semiconductor chip 22 and the reference current output terminal 9 of the first semiconductor chip 20 are placed so as to be close to each other. Thus, variation in output currents in each semiconductor chip can be suppressed to a low level.

[0084]

Moreover, the respective reference current supply sections of the first semiconductor chips 20 of FIGS. 1 and 2 and the second semiconductor chips 22 of FIGS. 1 and 2 have slightly different configurations. However, in semiconductor chips used in a display device, the configurations of reference current supply sections may be formed the same.

[0085]

FIG. 3 is a circuit diagram illustrating a connection portion of two chips each including a current driving device according to a modified example of the first embodiment. In the modified example of the first embodiment of FIG. 3, a first reference current input terminal **11a1** and a second reference current input terminal **11b1** are provided in the vicinity of an end portion of the first semiconductor chip **20**. Moreover, a reference current supply section has the same configuration as that of the reference current supply section of the second semiconductor chip **22** of FIG. 2 but is connected to the first reference current input terminal **11a1** and the second reference current input terminal **11b1** unlike the reference current supply section of the second semiconductor chip **22**.

[0086]

Specifically, in the first semiconductor of this modified example, provided are an n-channel eighth MISFET **33a1** connected to the second reference current input terminal **11b1**, an n-channel ninth MISFET **35a1** which is cascoded to the eighth MISFET **33a1** and has a gate electrode connected to the first reference current input terminal **11a1**, an n-channel tenth MISFET **37a1** constituting a current mirror circuit together with the eighth MISFET **33a1**, an n-channel eleventh MISFET **39a1** which is cascoded to the tenth MISFET **37a1** and constitutes a current mirror circuit together with the ninth MISFET **35a1**, and a p-channel first MISFET **1** for receiving a reference current flowing in the tenth MISFET **37a1**. Then, each of respective gate electrodes of the first and second MISFETs **1** and **2**, a drain of the first MISFET **1** and a drain of the tenth MISFET **37a1** is connected to the first reference current input terminal **11a1**.

[0087]

In this modified example, the first and second semiconductor chips **20** and **22** have the same configuration. However, in the first semiconductor chip **20**, the first reference current input terminal **11a1** is connected to a grounded resistance **16** (or a reference current

source) and the second reference current terminal **11b1** is grounded while in the second semiconductor chip **22**, the first reference current input terminal **11a2** is in an open state and the second reference current input terminal **11b2** is connected to the reference current output terminal **9** of the first semiconductor chip **20**.

5 [0088]

With the semiconductor chips of this modified example, a display panel can be driven using chips of a single type. Therefore, fabrication costs for a display device can be reduced.

[0089]

10 Note that in the exemplary semiconductor chips or current driving device described above, the MISFETs each constituting the current sources **5-1**, **5-2**, ... and **5-m** are of the n-channel type. However, the MISFETs can be operated in the same manner even if the MISFETs are of the p-channel type. In such a case, the conductive type of each of MISFETs constituting the reference current supply section and the current transmission
15 MISFET may be changed to the other conductive type.

[0090]

Note that when a plurality of semiconductor chips according to this modified example are cascaded, a resistance having the same resistance value as that of the resistance **16** may be connected to a reference current output terminal of a semiconductor
20 chip to be the final stage.

[0091]

Moreover, in the current driving device of this embodiment, a value for an current output from the reference current output terminal **9** of the first semiconductor chip **20** is not necessarily equal to a value for a reference current flowing in the reference current
25 source **4**. A current output from the reference current output terminal **9** is a reference

current (referred to as a “second reference current) for the second semiconductor chip 22. Then, if a current mirror circuit having an appropriate mirror ratio is provided between the reference current input terminal 11 and the seventh MISFET 23, the same amount of a current can be supplied to each of the MISFETs in the current sources constituting the current supply section 40 and each of the MISFETs in the current sources constituting the current supply section 41.

[0092]

(Second Embodiment)

FIG. 4 is a circuit diagram illustrating a current driving device according to a second embodiment of the present invention. The current driving device of this embodiment is characterized in that in addition to the components of the known current driving device shown in FIG. 21, current distribution MISFETs 55 and current input MISFETs 57 for transmitting a reference current to each of current supply sections 59 are provided. In this case, a “current supply section 59” means to be each of the current supply sections 59-1 through 59-m shown in FIG. 4. A “current distribution MISFET 55” means to be each of current distribution MISFETs 55-1 through 55-m shown in FIG. 4. And a “current input MISFET 57” means to be each of current input MISFETs 57-1 through 57-m shown in FIG. 4.

[0093]

As shown in FIG. 4, the current driving device of this embodiment includes a p-channel first MISFET 53, a reference current source 58 which is connected to the first MISFET 53 and generates a reference current, p-channel current distribution MISFETs 55-1, 55-2, ... and 55-n which constitute a current mirror circuit together with the first MISFET 53 and distribute a reference current, n-channel current input MISFETs 57-1, 57-2, ... and 57-n connected to the current distribution MISFETs 55-1, 55-2, ... and 55-n,

respectively, and current supply sections **59-1**, **59-2**, ... and **59-n** in which reference currents are transmitted from the current input MISFETs **57-1**, **57-2**, ... and **57-n** via a current mirror and which supply a driving current to pixel circuits (not shown). In this case, n is the number of outputs per a semiconductor chip. Moreover, respective gate electrodes of the first MISFET **53** and respective gate electrodes of the current distribution MISFETs **55-1**, **55-2**, ... and **55-n** are connected to a shared bias line **56**.

[0094]

Moreover, the respective configurations of the current supply sections **59-1**, **59-2**, ... and **59-n** is substantially the same as those in the current supply section **40** (see FIG. 1) described in the first embodiment. For example, the current supply section **59-1** includes an current input MISFET **57-1** and m current sources each being formed of one or more MISFETs constituting a current mirror circuit together with the current input MISFET **57-1**, and a switch (not shown) for turning ON or OFF a current flowing in the current source. However, respective gate electrodes of ones of the MISFETs constituting the current source which are connected to different output terminals do not have to be connected to one another, unlike the configuration of FIG. 4 and also may be connected to one another as described later.

[0095]

When each of the current supply sections **59** includes m current sources, a 2^m gray scale display can be performed. In an example shown in FIG. 4, although not shown in FIG. 4, each of the current supply sections **59** includes current sources of 6 bits and is formed of 63 MISFETs having the same size. Note that in FIG. 4, each of the current supply sections **59** and the current input MISFET are shown as a unit referred to as a "current supply unit **51**". In this case, the "current supply unit **51**" means to be each of current supply units **51-1** through **51-m**.

[0096]

In the current driving device of this embodiment, the current distribution MISFET 55 and the current input MISFET 57 for distributing a reference current are provided in each of the current supply sections 59. Thus, when a display device changes its state from a black display state to a white display state, with a current flowing from the panel side, an operation of a current source in the current supply section 59 is hardly affected. Specifically, in the current driving device of this embodiment, the current distribution MISFETs 55 and the current input MISFETs 57 are provided in each current supply section, so that the number of gate electrodes of MISFETs connected to one unit of the current distribution MISFET 55 and the current input MISFET 57 is less than that in the known current driving device. Thus, the capacitance of a bias interconnect connecting a gate electrode of each of the current input MISFETs 57 and a gate electrode of one of the MISFETs constituting a current source of the current supply sections 59 is reduced. Accordingly, change in the potential of the gate electrode of the MISFETs constituting a current source in the current supply sections 59 can be easily absorbed. As a result, change in an output of each of the current supply sections 59 can be suppressed.

[0097]

For the same reason, when a white display is changed to a black display, each of the current distribution MISFETs 55 is not affected and can distribute a constant current to the current supply sections 59 at all the time.

[0098]

Accordingly, with the current driving device of this embodiment, change in a gate potential of current source MISFETs in the current supply sections 59 is rapidly converges during a display data writing period. Therefore, a current driving type display device in which the generation of a crosstalk is suppressed and less display distortion occurs can be

achieved.

[0099]

Moreover, the reference current input and output terminals described in the first embodiment are provided in a semiconductor chip in which the current driving device of this embodiment is provided, thereby achieving a display device in which display distortion and nonuniformity can be further suppressed.

[0100]

FIG. 5 is a diagram illustrating semiconductor chips according to this embodiment in the case where each of reference current input and output terminals is provided at one end of each of the semiconductor chips.

[0101]

In each of a first semiconductor chip **70** and a second semiconductor chip **72** of FIG. 5, the current driving device of this embodiment, which has been described, is provided. Then, in the first semiconductor chip **70**, provided are a p-channel current transmission MISFET **61** constituting a current mirror circuit together with the distribution MISFETs **55** and the first MISFET **53**, and a reference current output terminal **9** connected to a current transmission MISFET **61**.

[0102]

On the other hand, in the second semiconductor chip **72**, provided are a reference current input terminal **11** connected to a reference current output terminal **9**, an n-channel eighth MISFET **33** connected to the reference current input terminal **11**, an n-channel ninth MISFET **35** which is cascoded to the eighth MISFET **33** and has a gate electrode connected to the reference current input terminal **11**, an n-channel tenth MISFET **37** constituting a current mirror circuit together with the eighth MISFET **33**, an n-channel eleventh MISFET **39** which is cascoded to the tenth MISFET **37** and constitutes a current

mirror circuit together with the ninth MISFET 35, a p-channel twelfth MISFET 43 for receiving a reference current flowing in the tenth MISFET 37, and the reference current terminal 9 (not shown). Note that in this case, each member also shown in FIG. 2 in the first embodiment is identified by the same name and the same reference numeral.

5 [0103]

Moreover, the reference current output terminal 9 is placed, for example, in the vicinity of an end portion of each of the first and second semiconductor chips 70 and 72. Furthermore, the distance between the reference current output terminal 9 and the current transmission MISFET 61 is about 100 μm or less. Moreover, the reference current input

10 terminal 11 is placed, for example, in the vicinity of an end portion of the second chip 72 so as to face the reference current output terminal 9 of the first semiconductor chip 70. Then, the distance between the reference current input terminal 11 and an MISFET such as the twelfth MISFET 43 constituting a reference current supply section is about 100 μm or less.

15 [0104]

A reference current generated in the reference current source 58 and the first MISFET 53 is transmitted to the current transmission MISFET 61 via a current mirror and is output from the reference current output terminal 9. Subsequently, the reference current is input to the reference current input terminal 11 and is input to the twelfth MISFET 43

20 via the eighth MISFET 33, the ninth MISFET 35, the tenth MISFET 37 and the eleventh MISFET 39. Then, the reference current is transmitted to a current transmission MISFET (not shown) which is provided on the second semiconductor chip 72 and constitutes a current mirror circuit together with the twelfth MISFET 43. The reference current transmitted to the current transmission MISFET is further transmitted to a semiconductor

25 chip in a subsequent stage via the reference current output terminal 9 (not shown).

[0105]

With the above-described configuration, a reference current with a small error is transmitted from the reference current output terminal **9** to the reference current input terminal **11**, the reference current output terminal **9** and the reference input terminal **11** being close to each other. Thus, it is possible to suppress the generation of a crosstalk and also suppress variation in output currents in each semiconductor chip including a current driving device to a low level in a semiconductor chip.

[0106]

Accordingly, with the above-described input/output configuration of a reference current, an image display with less nonuniformity can be achieved. Therefore, a large-size and high definition organic EL or LED display panel or the like can be achieved.

[0107]

Moreover, although not shown in FIG. **5**, with the reference current supply section having the same configuration as that of the example of FIG. **3**, semiconductor chips of only one type can be used in a display device. Therefore, fabrication costs for the display device can be reduced.

[0108]

Note that in the current driving device of this embodiment, the example in which the current distribution MISFETs **55** and the current input MISFETs **57** are provided in each of the current supply sections **59** is shown in FIG. **4**. However, a unit of the current distribution MISFET **55** and the current input MISFET **57** may be provided in every two or more current supply sections **59**. In such a case, two or more units of the current distribution MISFET **55** and the current input MISFET **57** can be provided in each semiconductor chip. The greater the number of current distribution MISFETs **55** is, the greater the effect of suppressing a crosstalk becomes. However, in an actual circuit, it is

preferable to take a balance between circuit area and performance of the circuit in designing the circuit.

[0109]

FIG. 6 is a circuit diagram illustrating a modified example of the current driving device of this embodiment. In a semiconductor chip, respective thresholds V_t of MISFETs arranged along the direction from a reference current input terminal to a reference current output terminal (i.e., the longitudinal direction of the chip) are graded due to an impurity-concentration gradient and the like, for example, so that the thresholds of ones of the MISFETs closer to the input terminal are high whereas the thresholds of ones of the MISFETs closer to the output terminal are low.

[0110]

Then, as shown in FIG. 6, in the current driving device of this embodiment, respective gate electrodes of ones of the MISFETs for constituting current sources in the current supply sections 59-1 through 59-n connected to different output terminals may be connected to one another, and also gate electrodes of the current input MISFETs 57 connected to different output terminals may be connected to one another. In such a case, a voltage may be applied to each of the gate electrodes of the MISFETs so that applied voltages are graded according to the gradient of the thresholds of the MISFETs. Thus, variation in currents output from the current supply sections 59 can be reduced. Note that in this modified example, an n-channel current transmission MISFET 66 constituting a current mirror circuit together with each of the current input MISFETs 57 and MISFETs in each of the current supply sections 59, and a reference current output terminal 9 connected to the current transmission MISFET 66 are provided to be connected to a semiconductor chip in a subsequent stage. At this time, if the current transmission MISFET 66 and the reference current output terminal 9 are placed in the vicinity of an end portion of a

semiconductor chip, variation in output currents in each semiconductor chip can be reduced as in the example of FIG. 3.

[0111]

(Third Embodiment)

5 FIG. 7 is a circuit diagram illustrating a current driving device according to a third embodiment of the present invention. FIGS. 8(a) and 8(b) are enlarged circuit diagrams illustrating exemplary configurations for a current supply unit 51 in the current driving device of this embodiment.

[0112]

10 As shown in FIG. 7, the current driving device of this embodiment includes a plurality of current distribution MISFETs as in the current driving device of the second embodiment. However, the current driving device of this embodiment is different from that of the second embodiment in the following points. Those points are features of the current driving device of this embodiment.

15 [0113]

First, a first feature of the current driving device of this embodiment is that an n-channel cascode MISFET 77 to be cascoded to one or more n-channel MISFETs serving as a current source in each of the current supply sections 59 is provided. In FIG. 7, a simplified configuration of each of the current supply sections 59 is illustrated. However, 20 each of the current supply section 59 actually has a configuration shown in FIG. 8(a) or 8(b).

[0114]

In an example shown in FIG. 8(a), for current sources 60-1, 60-2, ... and 60-m of m bits, a cascode MISFET 77 is provided via switches 64-1, 64-2, ... and 64-m. A gate 25 voltage **V_{clp}** of the cascode MISFET 77 is set at a lower level than a power supply voltage

(e.g., about 3 V) of a display panel. Moreover, the threshold of the cascode MISFET 77 is equal to or lower than the gate voltage **V_{clp}** and the cascode MISFET 77 is in an ON state during an entire driving period.

[0115]

5 Thus, the cascode MISFET 77 functions as a clamp circuit and can limit a current inflow from the panel side when non-conductive states of the switches **64-1**, **64-2**, ... and **64-m** are changed to conductive states at a time. Specifically, the gate voltage **V_{clp}** is set at a lower level than the power supply voltage of the display panel, so that even with a high voltage momentarily applied to an output terminal **68** from the display panel side, a voltage
10 applied to the drain of each of the MISFETs constituting the current sources **60-1**, **60-2**, ... and **60-m**, respectively, can be made equal to or lower than the gate voltage **V_{clp}**. Accordingly, the gate potential of each of the MISFETs constituting the current sources **60-1**, **60-2**, ... and **60-m**, respectively, is hardly affected by change in current inflow from the display panel. Therefore, in the current driving device of this embodiment, the
15 generation of a crosstalk display can be suppressed, thus achieving a uniform display.

[0116]

 Note that as current control means, a resistance element such as polysilicon resistance, diffusion resistance, well resistance and the like may be provided, instead of the cascode MISFET 77. In a semiconductor integrated circuit, in general, a current limiting
20 resistance for preventing an inflow of charge from the outside is provided to protect an internal circuit from electrostatic destruction. In this case, the resistance limits an inflow of charge from the display panel and removes high-frequency components. Then, high-frequency components have been removed, so that a parasitic capacitance between the drain and gate of each of the MISFETs serving as a current source can be reduced.
25 Therefore, change in the gate potential due to charge inflow from the panel can be

suppressed.

[0117]

Moreover, a current supply section in the current driving device of this embodiment may have the configuration shown in FIG. 8(b). In this example, cascode MISFETs 77-1, 77-2, ... and 77-m are provided, instead of switches (corresponding to the switches 64-1 through 64-m in FIG. 8(a)) for controlling the amount of a current flowing in each of the current supply sections 59. The gate voltage V_{clp} lower than the power supply voltage of the display panel is applied to each of the cascode MISFETs 77-1, 77-2, ... and 77-m to turn ON each of the cascode MISFETs 77-1, 77-2, ... and 77-m. Note that each of the cascode MISFETs 77-1, 77-2, ... and 77-m also functions as an output control switch of each of the current supply sections 59. Accordingly, the cascode MISFET 77-1, 77-2, ... and 77-m are controlled to be ON or OFF according to display data.

[0118]

Thus, the cascode MISFETs 77-1, 77-2, ... and 77-m function to prevent a rapid flow of a high current in the current sources of each of the current supply sections 59 when a black display is changed to a white display and the like. Furthermore, with this configuration, a circuit area can be reduced, compared to the example of FIG. 8(a). Therefore, the current driving device of this embodiment is preferably used for a display device including a driver LSI of which the area is required to be small.

[0119]

Next, a second feature of the current driving device of this embodiment is that second current distribution MISFETs 73 each of which is cascoded to on associated one of current distribution MISFETs 55 and has the same conductivity type as that of the current distribution MISFETs 55 is provided between the associated one of the p-channel current distribution MISFETs 55 and an associated one of current input MISFETs 57. Thus, the

current driving device of this embodiment includes a p-channel thirteenth MISFET 71 provided between the drain of a first MISFET 53 and a reference current source 58, and a p-channel fourth current transmission MISFET 75 which is cascoded to the current transmission MISFET 61 and constitutes a current mirror circuit together with the thirteenth MISFET 71. Each of gate electrodes of the second current distribution MISFETs 73 is connected to a shared bias line and the second current distribution MISFETs 73 constitutes a current mirror circuit together with the thirteenth MISFET 71 and the fourth transmission MISFET 75. Herein, the “second current distribution MISFETs 73” is an expression used when the second current distribution MISFETs 73-1 through 73-m are not distinguished from one another.

[0120]

With the above-described configuration, in the current driving device of this embodiment, change in a reference current transmitted to each of the current sources 60-1 through 60-m of each of the current supply sections 59 via each of the current input MISFETs 57 is suppressed and thus stabilized. Therefore, with the current driving device of this embodiment, display quality of the current driving type display device can be further improved.

[0121]

Next, a third feature of the current driving device of this embodiment is that a reference current output terminal 9 is provided in the vicinity of an end portion of the semiconductor chip 70 and a reference current input terminal 11 is provided in the vicinity of the semiconductor chip 72 and n-channel current transmission MISFETs 79 and 81 together constituting a current mirror circuit are provided in the vicinity of the end portion of the semiconductor chip 70. Furthermore, in an example shown in FIG. 7, when the reference current source 58 is located outside of the first semiconductor chip 70 and a

reference current input terminal is provided between the reference current source 58 and the drain of the thirteen MISFET 71, the first and second semiconductor chips 70 and 72 can be made to have the same configuration.

[0122]

5 Thus, variation in output currents between semiconductor chips can be suppressed and also a driver of a display device can be formed of semiconductor chips of a single type.

[0123]

Note that the example of the current driving device of this embodiment which has the above-described three features has been described. However, even when the current
10 driving device has one or two of these features, a more uniform display can be achieved, compared to the known current driving device.

[0124]

Note that in the current driving device of this embodiment, the conductive type of each of the MISFETs in each of the current supply sections 59 may be the p-channel, and
15 the potential in the current supply sections 59 side may be higher than that of the display panel. In such a case, the conductive type of each of the MISFETs constituting the current driving device can be changed to the other conductive type. This can be done in the following embodiments as well.

[0125]

20 (Fourth Embodiment)

FIG. 9 is a circuit diagram illustrating a current driving device according to a fourth embodiment of the present invention.

[0126]

As shown in FIG. 9, the current driving device of this embodiment is characterized
25 in that in the current driving device of the second embodiment, a reference current

distributed by a current mirror including the current distribution MISFETs **55** is arbitrarily changed (i.e., shuffled) output from an output terminal of each of the current supply sections **59**. Thus, the internal circuit configuration of each of the current supply units **51-1** through **51-n** in the current driving device of this embodiment is the same as that in the second embodiment.

[0127]

In an example of the current driving device of this embodiment shown in FIG. **9**, each of the current distribution MISFETs **55** is provided for each of the current supply sections **59** and first and second bias current changing switches **91** and **92** are provided between the drain of each of the current distribution MISFETs **55** and each of the current input MISFETs **57**. For example, first and second bias current changing switches **91-1** and **92-1** are provided between a current distribution MISFET **55-1** and a current input MISFET **57-1** and first and second bias current changing switches **91-2** and **92-2** are provided between a current distribution MISFET **55-2** and a current input MISFET **57-2**.

[0128]

With this configuration, a reference current distributed by each of current distribution MISFETs **55-1** through **55-n** can be output from a different output terminal of the current supply sections **59** in every arbitrary period. A timing of changing connections between the first bias current changing switches **91** and the second bias current changing switches **92** can be arbitrarily set, for example, every n lines (n is a positive integer), every frame or the like.

[0129]

FIGS. **10(a)**, **10(b)** and **10(c)** are circuit diagrams illustrating an example of output changing methods in the current driving device of this embodiment. FIGS. **11(a)**, **11(b)** and **11(c)** are circuit diagrams illustrating another example of output changing methods in

the current driving device of this embodiment.

[0130]

Focusing on one of the current distribution MISFETs **55**, FIGS. **10(a)**, **10(b)** and **10(c)** illustrate a method for changing connections of the current distribution MISFETs **55** to the current supply units **51**. If connections are changed among the current distribution MISFETs **55**, dummy current distribution MISFETs **95** and **99** can be provided next to the current distribution MISFET **55-1** and the current distribution MISFET **55-n**, respectively, so that the current distribution MISFETs **55-1** through **55-n** are interposed between the dummy current distribution MISFETs **95** and **99**. In this case, dummy bias current changing switches **96**, **97**, **100** and **101** are also provided.

[0131]

The current distribution MISFET **55-1** will be taken as an example to describe this method. Here, an example in which connection change is performed in every horizontal scanning period will be described.

[0132]

First, in an initial horizontal scanning period, the current distribution MISFET **55-1** is connected to the current supply unit **51-1** in a normal manner as shown in FIG. **10(a)**.

[0133]

In the subsequent horizontal scanning period, the current distribution MISFET **55-1** is connected to the current supply unit **51-2** as shown in FIG. **10(b)**.

[0134]

In a further subsequent horizontal scanning period, the current distribution MISFET **55-1** is connected to a dummy interconnect as shown in FIG. **10(c)**. Note that only the current distribution MISFET **55-1** has been described herein, but connections in other part of the current distribution MISFETs **55** are also changed in the same manner.

[0135]

As described above, the relationship between the current distribution MISFETs **55** and an output current can be changed in three different ways. Thus, variation in properties of the current distribution MISFETs **55** can be cancelled off. Therefore, with the current driving device of this embodiment, a current driving type display device in which display flicker is suppressed can be achieved. Note that in the example of FIG. **10**, three connection changing patterns of FIGS. **10(a)**, **10(b)** and **10(c)** are used. However, more than three patterns may be used or only two patterns shown in FIGS. **10(b)** and **10(c)** may be used.

[0136]

Moreover, the current driving device of this embodiment can perform another connection changing method shown in FIGS. **11(a)**, **11(b)** and **11(c)**.

[0137]

Specifically, in an initial horizontal scanning period, the current distribution MISFET **55-1** is connected to a current supply unit **51-3** as shown in FIG. **11(a)**.

[0138]

Then, in the subsequent horizontal scanning period, the current distribution MISFET **55-1** is connected to a current supply unit **51-2** as shown in FIG. **11(b)**.

[0139]

In a further subsequent horizontal scanning period, the current distribution MISFET **55-1** is connected to a dummy bias current changing switch **97b** as shown in FIG. **11(c)**. In this connection changing method, an error in output currents from the current supply sections **59** is apparently cancelled off.

[0140]

Note that in the current driving device of this embodiment, the connection changing

method for changing a connection of the current distribution MISFETs 55 is not limited to the methods described above, but the current supply units 51 in which connections of the current distribution MISFETs 55-1 through 55-n take place can be arbitrarily changed. However, each of the current distribution MISFETs 55 is more preferably connected to
5 each of the second bias current changing switches 92 located in the vicinity of the current distribution MISFETs 55 as possible because an interconnect can be short and simplified with such a connection. Therefore, it is the most preferable to change a connection between current distribution MISFETs 55 located adjacent to each other.

[0041]

10 Note that in the current driving device of this embodiment, the bias current changing switches 91 and 92 for changing a connection between output terminals is provided between each of the distribution MISFETs 55 and each of the current input MISFETs 57. However, the first and second bias current changing switches 91 and 92 may be provided between the drain of the n-channel MISFETs constituting each of the
15 current supply section 59-1 and each of the switches 64 (see FIG. 8).

[0142]

Moreover, in the current driving device shown in FIGS. 9 through 11, a switch (or a connection changing terminal) is used as the connection changing means for changing the connection between each of the current distribution MISFETs 55 and each of the current
20 input MISFETs 57. However, some other connection changing means may be provided.

[0143]

Note that in the current driving device of this embodiment, when a circuit area is limited, the current distribution MISFETs 55 and the current input MISFETs 57 may be provided so that one current distribution MISFET 55 and one current input MISFET 57 are
25 located per a plurality of the current supply sections 59.

[0144]

- Modified Example of Fourth Embodiment -

FIG. 12 is a circuit diagram illustrating a current driving device and a semiconductor chip according to a modified example of the fourth embodiment of the present invention.

[0145]

The current driving device of this modified example has substantially the same configuration as that of the current driving device of FIG. 9. However, this modified example is different from the fourth embodiment in that a first terminal 160 connected to a first bias current changing switch 91-n and a second terminal 162 connected to a second bias current changing switch 92-n are provided in the first semiconductor chip 70. Moreover, in a second semiconductor chip 72, a third terminal 164 connected to a first bias current changing switch 91-1 and a fourth terminal 166 connected to a second bias current switch 92-1 are further provided in addition to the first and second terminals 161 and 162.

[0146]

Thus, when a plurality of semiconductor chips each including the current driving device of this modified example are arranged, connection change can be performed not only between the current distribution MISFETs 55 and the current input MISFETs in a single semiconductor chip but also between the current distribution MISFETs 55 and the current input MISFETs provided on semiconductor chips adjacent to each other, respectively. Note that in the example shown in FIG. 12, the first terminal 160 is connected to the first bias current changing switch 91-n and the second terminal 162 is connected to the second bias current changing switch 92-n, but the first and second terminals 160 and 162 may be designed to be connected to first and second bias current changing switches 91 and 92 located at a more distance from the first and second terminals

160 and 162, respectively.

[0147]

The current driving device of this modified example is driven in the above-described manner, so that not only variation in output currents from output terminals in a semiconductor chip but also variation in output currents between semiconductor chips can
5 be reduced.

[0148]

(Fifth Embodiment)

FIG. 13 is a diagram illustrating the configuration of a current supply section in a first example of a current driving device according to a fifth the embodiment of the present
10 invention.

[0149]

In each of the current driving devices of the first through fourth embodiments of the present invention, MISFETs constituting current supply sections 59-1, 59-2 and 59-3, respectively, are arranged as shown in FIG. 13, so that ones of the MISFETs constituting
15 each of current supply sections are located together in many cases. In the following description, in a region of a current driving device in which MISFETs are provided, part of the region in which one or more of the MISFETs constituting the current supply section 59-1 is referred to as a “first MISFET region 76-1”, part of the region in which one or
20 more of the MISFETs constituting the current supply section 59-2 is referred to as a “second MISFET region 76-2”, and part of the region in which one or more of the MISFETs constituting the current supply section 59-3 is referred to as a “third MISFET region 76-3”. Note that these parts are referred to as “MISFET regions 76” when the first through third MISFETs regions are not distinguished from one another. Note that although
25 not shown in FIG. 14, 16 MISFETs and 32 MISFETs all having the same size are further

provided in the MISFET region 76.

[0150]

The current driving device of this example is characterized in that each of current supply sections 59 includes MISFETs provided in different MISFET regions 76 in a current driving device having the circuit arrangement described above.

[0151]

As for the MISFETs constituting each of the current supply sections 59, property variation caused due to differences in locations of the MISFETs in a semiconductor chip, in fabrication process steps, and the like is found. Specifically, property variation between MISFETs located in different MISFET regions is relatively large. In the current driving device of this example, output currents are shuffled between adjacent output terminals or between output terminals located apart from each other to average property variation of the MISFETs constituting the current supply section 59. Thus variation in output currents between output terminals can be suppressed. Therefore, with the current deriving device of this example used for a display device, display nonuniformity can be suppressed, thus resulting in improved display quality.

[0152]

Note that in the current driving device of this example, MISFETs in arbitrary MISFET regions 76 in a semiconductor chip may be combined to form current supply sections 59. However, as shown in FIG. 13, it is preferable to combine MISFETs in MISFET regions adjacent to each other because an interconnection becomes simple. To make output currents further uniform, however, it is necessary to combine MISFETs in MISFET regions located apart from each other. Therefore, a design is actually made taking a balance between simplicity of interconnects and the effect of reducing variation into consideration. In any case, combinations for connections between MISFETs in the

MISFETs regions and output terminals of the current supply sections 59 may be determined in designing a circuit by using a random number.

[0153]

Moreover, FIG. 14 is a diagram illustrating the configuration of a current supply section in a second example of the current driving device of the fifth embodiment.

[0154]

In the current driving device of the first example, the arrangement of MISFETs serving as a current source according to bits in each of the MISFET regions 76 is fixed (see FIG. 13).

[0155]

In contrast, in the current driving device of this example, as shown in a layout in an upper part of FIG. 14, gate electrodes of arbitrary MISFETs provided in the MISFET regions 76 are connected to one another to form each of the current supply sections 59. In other words, in the current driving device of this example, selection of MISFETs constituting a current source is changed at random in every output terminal.

[0156]

Even between MISFETs provided in a single one of MISFET regions 76, property variation occurs depending on the locations of the MISFETs. Therefore, as in this example, if the current supply section 59 includes MISFETs selected at random from MISFETs provided in the MISFET regions 76, variation in output currents can be made further uniform and suppressed, compared to the first example. Thus, with the current driving device of this example used for a display device, display nonuniformity can be suppressed and display quality can be improved. Moreover, an area for switches to be provided is no longer necessary. Therefore, a circuit area can be reduced, compared to the fourth embodiment.

[0157]

Note that the circuit arrangement and interconnection configuration in each of the current driving devices of the first and second examples are not limited to the first through fourth embodiments, but can be applied to the known current driving device of FIG. 20 to obtain the same effects. Moreover, if the interconnection configuration is applied to the fourth embodiment, an error in currents by output terminals can be remarkably reduced.

[0138]

(Sixth Embodiment)

FIG. 15 is a circuit diagram illustrating a current driving device according to a sixth embodiment of the present invention.

[0159]

As shown in FIG. 15, the current driving device of this embodiment is characterized in that resistances 62 are provided on a bias line 56 and between gate electrodes of adjacent ones of current distribution MISFETs 55 in the second current driving device of FIG. 4. Herein, the “resistances 62” is an expression used when resistances 62-1, 62-2, ..., and 62-(n-1) are not distinguished to one another. Note that a current source or an interconnect (not shown) for causing potential gradient is connected to the reference current output terminal side of the bias line 56 of FIG. 15.

[0160]

In the current driving device of this embodiment, the resistances 62 are provided, so that an error in output currents can be reduced between output terminals. This will be described hereinafter.

[0161]

A current mirror circuit is provided on the assumption that diffusion conditions for transistors constituting the current mirror circuit are the same and thus there is no

significant difference in threshold V_t and carrier mobility. However, if the length of a chip of the display device driver LSI is 10-20 mm, it seems difficult to uniformly diffuse an impurity contained in each of the transistors. As a result, the threshold of a transistor to serve as a current mirror varies, thus resulting in variation in output currents. Normally, the diffusion change shows gradual increase or decrease in a wafer surface. Thus, for example, the threshold V_t of the current distribution MISFETs **55** decreases along the direction from the current distribution MISFET **55-1** to the current distribution MISFET **55-n**.

[0162]

In the current driving device of this embodiment, the resistances **62** are provided on the bias line **56**. Thus, a gate voltage applied to each of the current distribution MISFETs **55-1** through **55-n** can be varied according to the gradient of the threshold V_t . As a result, a value for a current flowing in the current distribution MISFETs **55** can be made constant.

[0163]

Therefore, with the current driving device of this embodiment, variation in output currents from the current supply sections **59** in a semiconductor chip can be suppressed and thus quality of a display device can be improved.

[0164]

Note that for the current driving device of this embodiment, the configuration of the reference current input and output terminals described in the first embodiment and the configurations described in the fourth and fifth embodiments may be adopted together.

[0165]

(Seventh Embodiment)

FIG. **16** is a circuit diagram illustrating a current driving device according to a seventh embodiment of the present invention.

[0166]

As shown in FIG. 16, the current driving device of this embodiment has a configuration in which in addition to the components of the known current driving device of FIG. 20, a cascode MISFET **80** having the same conductive type as that of the MISFETs and forming a cascode connection together with the MISFETs is provided in each of MISFETs constituting a current source of each of current supply sections **59**. The configuration of the current supply sections **59** of FIG. 16 seems similar to that of the current supply sections **59** of FIG. 7. However, the configuration of the current supply sections **59** of FIG. 16 is different from that of the current supply sections **59** of FIG. 7 in that cascode MISFETs **80** are provided so that each of the cascode MISFETs **80** is located for one or more MISFETs constituting a current source, a switch **64** for gray scale control of an output current is provided between each of the cascode MISFETs **80** and an output terminal (not shown), and furthermore, respective gate electrodes of the cascode MISFETs **80** are connected to the gate electrode of a second current input MISFET **105** so that the gate electrodes of the cascode MISFETs **80** share the gate electrode of the second current input MISFET **105**. The drain of the second current input MISFET **105** and each of the gate electrodes are connected to one another and a setting is made so that a reference current can flow therethrough. Moreover, the cascode MISFETs **80** constitute a current mirror circuit together with the second current input MISFET **105**. For example, a second current distribution MISFET (not shown) for distributing a reference current is connected to the drain of the second current input MISFET **105**.

[0167]

Thus, in each section of the current supply section **59** to be described in this embodiment, a bias voltage is applied from both of the current input MISFET **57** side and the second current input MISFET **105**.

[0168]

With this configuration, for an output current of each of the current supply sections 59, a current to flow in MISFETs constituting a current source (i.e., current source MISFETs) when the cascode MISFETs 80 are not connected to the MISFETs and a current to flow therein when the cascode MISFETs 80 are provided alone are averaged. Although gate voltages at the same level are applied to all of the current source MISFETs and also gate voltages at the same level are applied to all of the cascode MISFETs 80, the respective thresholds of the current source MISFETs and the cascode MISFETs 80 vary depending on the respective locations of the current source MISFETs and the cascode MISFETs 80 on the semiconductor chip, so that the threshold of the current source MISFETs has a gradient in an opposite direction from that of the threshold of the cascode MISFETs 80, i.e., from right to left in FIG. 16. Accordingly, by averaging a current to flow in the current source MISFETs and a current to flow in the cascode MISFETs 80, variation in output currents in each output terminal can be averaged, so that output currents from the output terminals can be made uniform. Therefore, with the current driving device of this embodiment, a high definition display device in which display nonuniformity is suppressed can be achieved.

[0169]

Note that in FIG. 16, the example in which a unit of the current input MISFET 57 and the current distribution MISFET (first MISFET) 55 and a unit of the second current input MISFET 105 and the second current distribution MISFET are provided in each semiconductor chip is shown. However, the example may be combined with another configuration shown in the description of the current driving device made in the second embodiment.

[0170]

FIG. 17 is a circuit diagram illustrating a current driving device obtained by

combining the current driving device of this embodiment with the current driving device of the second embodiment. In this current driving device, a plurality of units of the current input MISFET **57** and the current distribution MISFET **55** are provided.

[0171]

5 In this case, it is preferable to also provide a plurality of units of the second current input MISFET **105** and the second current distribution MISFET **55b** in each semiconductor chip. Specifically, if the number of units of the current input MISFET **57** and the current distribution MISFET **55** is the same as the number of units of the second current input MISFET **105** and the second current distribution MISFET **55b**, variation in
10 output currents in each output terminal can be effectively reduced. Thus, providing these units in the same number is particularly preferable. Note that the gate electrode of the second current distribution MISFET **55b** is connected to a shared bias line **56b**. With this configuration, the generation of a crosstalk display can be suppressed when the current driving device of this embodiment is used for a display device.

15 [0172]

Note that when the current driving device has this configuration, the configuration can be combined with the configurations described in the fourth and fifth embodiments. For example, the current driving device of FIG. **17** further includes connection changing means **130a** provided between each of the current distribution MISFETs **55** and each of the
20 current input MISFETs **57** and connection changing means **130b** provided between each of the second current distribution MISFETs **55** and the second current input MISFET **105**. The connection changing means **130a** connects one of the current distribution MISFETs **55** to a different one of the current input MISFETs **57** in each period which has been arbitrarily set. In the same manner, the connection changing means **130b** connects the
25 second current distribution MISFET **55b** to a different second current input MISFET **105**

in each period which has been arbitrarily set. Thus, output currents from the current supply sections **59** can be made further uniform.

[0173]

Moreover, the configuration of the current driving device of this embodiment may
5 be combined with the configuration described in the first embodiment.

[0174]

FIG. **18** is a circuit diagram illustrating the current driving device of this embodiment in the case where the current driving device has the terminal configuration described in the first embodiment. As shown in FIG. **18**, in the current driving device of
10 this embodiment, a first reference current input terminal **124** and a first reference current output terminal **126** can be provided in part of a semiconductor chip located at a distance of 200 μm or less, more preferably 100 μm or less, from one of the current input MISFETs **57**, and a second reference current input terminal **128** and a second reference current output terminal **130** can be provided in part of the semiconductor chip located at a distance
15 of 200 μm or less, more preferably 100 μm or less, from the second current input MISFET **105**. When a plurality of semiconductor chips each including a current driving device are arranged in a frame portion of a display panel, the first reference current output terminal **126** can be connected to the first reference current input terminal **124** in a second semiconductor chip **122** in a subsequent stage and the second reference current output
20 terminal **130** can be connected to the second reference current input terminal **128** in the second semiconductor chip. Thus, variation in output currents between semiconductor chips can be suppressed.

[0175]

(Eighth Embodiment)

25 FIG. **19** is a circuit diagram illustrating semiconductor chips each including a

current driving device according to an eighth embodiment of the present invention. In the current driving device of FIG. 19, the configuration of a current supply section 40 is the same as the current supply section 40 of FIG. 2. Therefore, the configuration of other components will be described.

5 [0176]

The semiconductor chips of this embodiment is characterized in that when the semiconductor chips are arranged, for example, in a row in a periphery portion of a display panel, the direction in which a reference current flows is changed in every arbitrary interval of time.

10 [0177]

As shown in FIG. 19, the current driving device of this embodiment includes a first reference current input terminal 146 connected to a reference current source 151 for making a first current flow, a first current input MISFET 3a which constitutes a current mirror circuit together with one or more MISFETs constituting each of current sources 5, in which a gate electrode and a drain are connected to each other and to which the first reference current is transmitted, a first current transmission MISFET 7b which constitutes a current mirror circuit together with the one or more MISFETs constituting each of the current sources 5 and the first current input MISFET 3a, a first reference current output terminal 150 to which an output current from the first current transmission MISFET 7b is transmitted, a second reference current input terminal 148 for receiving a second reference current output from a second reference current source 153 or a semiconductor chip in a subsequent stage, a second current input MISFET 36 which constitutes a current mirror circuit together with the one or more MISFETs constituting each of the current sources 5 and in which a gate electrode and a drain are connected to each other, a second current transmission MISFET 7a which constitutes a current mirror circuit together with the

15
20
25

second current input MISFET and the one or more MISFETs constituting each of the current sources **5**, a second reference current output terminal **144** to which an output current from the second current transmission MISFET **7a** is transmitted, a switch **SW1** connected to the second reference current output terminal **144**, a switch **SW2** connected to the first reference current input terminal **146**, a switch **SW3** connected to the second reference current input terminal **148**, and a switch **SW4** connected to the first reference current output terminal **150**. Moreover, a reference current changing switch **154** is provided on a current transmission path between the first reference current input terminal **146** and the first current input MISFET **3a** and a current transmission path between the second reference current output terminal **144** and the second current transmission MISFET **7a** and a reference current switch **156** is provided on a current transmission path between the second reference current input terminal **148** and the second current input MISFET **3b** and on a current transmission path between the first reference current output terminal **150** and the first current transmission MISFET **7b**.

[0178]

Moreover, the distance between the first reference current input terminal **146** and the first current input MISFET **3a** is preferably 200 μm or less, and more preferably 100 μm or less, and the distance between the first reference current output terminal **150** and the first current transmission MISFET **7b** is also preferably 200 μm or less, and more preferably 100 μm or less. In the same manner, the distance between the second reference current input terminal **148** and the second current input MISFET **3b** is preferably 200 μm or less, and more preferably 100 μm or less, and the distance between the second reference current output terminal **144** and the second current input MISFET **7a** is also preferably 200 μm or less, and more preferably 100 μm or less.

[0179]

Thus, when the semiconductor chips of this embodiment are cascaded, variation in output currents in each semiconductor chip (i.e., driving currents for a pixel circuit) can be reduced.

[0180]

5 Moreover, in a display device, when a first semiconductor chip **140** and a second semiconductor chip **142** are arranged so as to be adjacent to each other, the first reference current output terminal **150** of the first semiconductor chip **140** and the first reference current input terminal **146** of the second semiconductor chip **142** are connected to each other, and the second reference current input terminal **148** of the first semiconductor chip
10 **140** and the second reference current output terminal **144** of the second semiconductor chip **142** are connected to each other.

[0181]

In the current driving device of this embodiment, the switches **SW1** and **SW3** are synchronized with each other to operate and the switches **SW2** and **SW4** are synchronized
15 with each other to operate. In addition, operations of the switches **SW1** and **SW3** are controlled so that the switches **SW1** and **SW3** are in an ON state when the switches **SW2** and **SW4** are in an OFF state and vice versa. Then, when the current driving device of this embodiment is in an operation state, as will be described next, a first period in which a first reference current is transmitted to a plurality of semiconductor chips and a second period
20 in which a second reference current is transmitted to a plurality of semiconductor chips are alternately repeated.

[0182]

First, in the first period, as shown in FIG. **19**, the switches **SW2** and **SW4** are turned ON and the switches **SW1** and **SW3** are turned OFF while the reference current
25 switch **154** makes the current transmission path between the first reference current input

terminal **146** and the first current input MISFET **3a** conductive and cuts off the current transmission path between the second reference current output terminal **144** and the second current transmission MISFET **7b**. At the same time, the reference current switch **156** makes the current transmission path between the first reference current output terminal **150** and the first current transmission MISFET **7b** conductive and cuts off the current transmission path between the second reference current input terminal **148** and the second current input MISFET **3b**. By this control, a first reference current is transmitted to a plurality semiconductor chips via the first reference current input terminal **146** and the first reference current output terminal **150**.

[0183]

Next, in the second period, the switches **SW2** and **SW4** are turned OFF and the switches **SW1** and **SW3** are turned ON while the reference current switch **154** cuts off the current transmission path between the first reference current input terminal **146** and the first current input MISFET **3a** and makes the current transmission path between the second reference current output terminal **144** and the second current transmission MISFET **7b** conductive. At the same time, the reference current switch **156** cuts off the current transmission path between the first reference current output terminal **150** and the first current transmission MISFET **7b** and makes the current transmission path between the second reference current input terminal **148** and the second current input MISFET **3b** conductive. By this control, a second reference current supplied from the second reference current source **153** is transmitted to a plurality semiconductor chips via the second reference current input terminal **148** and the second reference current output terminal **144**.

[0184]

When driving a large screen display panel, it is necessary to arrange a plurality of semiconductor chips each including a current driving device. However, in the known

current driving device in which a reference current is supplied from only one direction, an error tends to appear between a reference current supplied to a semiconductor chip in an initial stage and a reference current transmitted to a semiconductor chip in a final stage. Compared to the known current driving device, in the current driving device of this embodiment, reference currents from two different reference current sources are alternately transmitted in every arbitrary period, so that variation in output currents from output terminals is averaged. Therefore, with the current driving device of this embodiment, even when a display panel is large-sized, a display device in which a display is made uniform can be achieved.

[0185]

Note that in FIG. 19, the configuration of the current supply section 40 is the same as that in the first embodiment. However, the current supply section 40 may have the same configuration as that of the current supply section in any one of the other embodiments as long as the configuration allows change in the direction in which a reference current flows.

[0186]

Moreover, the current transmission path between the first reference current input terminal 146 and the first current input MISFET 3a and the current transmission path between the second reference current output terminal 144 and the second current transmission MISFET 7b share part of each other. However, the current transmission path between the first reference current input terminal 146 and the first current input MISFET 3a and the current transmission path between the second reference current output terminal 144 and the second current transmission MISFET 7a may be provided separately. In such a case, no reference current switch is necessary. In the same manner, the current transmission path between the first reference current output terminal 150 and the first current transmission MISFET 7b and the current transmission path between the second

reference current input terminal **148** and the second current input MISFET **3b** may be provided separately.

[0187]

[Effects of the Invention]

5 In a current driving device according to the present invention, a plurality of current distribution MISFETs for distributing a reference current and a plurality of current input MISFETs are provided on each semiconductor chip, so that output impedances at gates of MISFETs constituting a current supply section can be relatively reduced. Therefore, if the current driving device of the present invention is used for a display device, change in the
10 gate potential of the MISFETs due to a current flowing from the display panel side can be suppressed. As a result, the generation of a crosstalk in the display device can be suppressed.

[FIG. 1]

FIG. 1 is a circuit diagram illustrating a connection portion of two chips each
15 including a current driving device according to a first embodiment of the present invention.

[FIG. 2]

FIG. 2 is a circuit diagram illustrating a connection portion of two chips each including an example of the current driving device of the first embodiment.

[FIG. 3]

20 FIG. 3 is a circuit diagram illustrating a connection portion of two chips each including a current driving device according to a modified example of the first embodiment.

[FIG. 4]

FIG. 4 is a circuit diagram illustrating a current driving device according to a
25 second embodiment of the present invention.

[FIG. 5]

FIG. 5 is a diagram illustrating semiconductor chips according to the second embodiment in the case where each of reference current input and output terminals is provided at one end and another of each of the semiconductor chips, respectively.

5 [FIG. 6]

FIG. 6 is a circuit diagram illustrating a modified example of the current driving device of the second embodiment.

[FIG. 7]

FIG. 7 is a circuit diagram illustrating a current driving device according to a third
10 embodiment of the present invention.

[FIG. 8]

FIGS. 8(a) and 8(b) are enlarged circuit diagrams illustrating exemplary configurations for a current supply unit 51 in the current driving device of the third embodiment.

15 [FIG. 9]

FIG. 9 is a circuit diagram illustrating a current driving device according to a fourth embodiment of the present invention.

[FIG. 10]

FIGS. 10(a), 10(b) and 10(c) are circuit diagrams illustrating an example of output
20 changing methods in the current driving device of the fourth embodiment.

[FIG. 11]

FIGS. 11(a), 11(b) and 11(c) are circuit diagrams illustrating another example of output changing methods in the current driving device of the fourth embodiment.

[FIG. 12]

25 FIG. 12 is a circuit diagram illustrating a current driving device and a

semiconductor chip according to a modified example of the fourth embodiment of the present invention.

[FIG. 13]

FIG. 13 is a diagram illustrating the configuration of a current supply section in a first example of a current driving device according to a fifth embodiment of the present invention.

[FIG. 14]

FIG. 14 is a diagram illustrating the configuration of a current supply section in a second example of the current driving device of the fifth embodiment.

10 [FIG. 15]

FIG. 15 is a circuit diagram illustrating a current driving device according to a sixth embodiment of the present invention.

[FIG. 16]

FIG. 16 is a circuit diagram illustrating a current driving device according to a seventh embodiment of the present invention.

[FIG. 17]

FIG. 17 is a circuit diagram illustrating a current driving device according to a first modified example of the seventh embodiment.

[FIG. 18]

20 FIG. 18 is a circuit diagram illustrating a current driving device according to a second modified example of the seventh embodiment.

[FIG. 19]

FIG. 19 is a circuit diagram illustrating semiconductor chips each including a current driving device according to an eighth embodiment of the present invention.

25 [FIG. 20]

FIG. 20 is a circuit diagram illustrating the configurations of a display panel and a known current driving device serving as a display driver connected to the display panel.

[FIG. 21]

FIG. 21(a) is a view illustrating an example of black and white displays in a display panel; FIG. 21(b) is a circuit diagram illustrating the pixel circuits arranged along the line
5 XX1b-XX1b of the display panel shown in FIG. 21(a) and known current supply sections connected to the pixel circuits, respectively; FIG. 21(c) is a graph showing an operating point of a TFT in a black display state; and FIG. 21(d) is a graph showing an operating point of a TFT in a white display state.

10 [FIG. 22]

FIG. 22(a) is a view illustrating an example of black and white displays in a display panel; FIG. 22(b) is a circuit diagram illustrating the pixel circuits arranged along the line
XX2b-XX2b of the display panel shown in FIG. 22(a) and known current supply sections connected to the pixel circuits, respectively; FIG. 22(c) is a graph showing an operating
15 point of a TFT when a black display is changed to a white display; and FIG. 22(d) is a graph showing an operating point of the TFT when a white display is continuously performed.

[FIG. 23]

FIG. 23 is a circuit diagram illustrating the arrangement and configuration of a
20 current supply section in the known current driving device.

[Explanation of the Reference Characters]

- | | |
|----------|--------------------------|
| 1, 53 | First MISFET |
| 2 | Second MISFET |
| 3 | Current input MISFET |
| 25 4, 58 | Reference current source |

	5, 5-1 ... 5-m, 25, 25-1 ... 25-m, 60	Current sources
	7	First current transmission MISFET
	9	Reference current output terminal
	10	Third current transmission MISFET
5	11	Reference current input terminal
	11a	First reference current input terminal
	11b	Second reference current input terminal
	12	Fourth current transmission MISFET
	13	Third MISFET
10	15	Fourth MISFET
	16	Resistance
	17	Fifth MISFET
	19	Sixth MISFET
	20	First semiconductor chip
15	22	Second semiconductor chip
	23	Seventh MISFET
	33, 33a	Eighth MISFET
	35, 35a	Ninth MISFET
	37, 37a	Tenth MISFET
20	39, 39a	Eleventh MISFET
	40, 41, 59, 59-1 ... 59-n	Current supply section
	43	Twelfth MISFET
	51, 55-1 ... 55-n	Current distribution MISFET
	56	Bias line
25	57, 57-1 ... 57-n	Current input MISFET

	61, 66, 79, 81	Current transmission MISFET
	62	Resistance
	64	Switch
	68	Output terminal
5	70	First semiconductor chip
	71	Thirteenth MISFET
	72	Second semiconductor chip
	73	Second current distribution MISFET
	75	Fourth current distribution MISFET
10	76	MISFET region
	76-1	First MISFET region
	76-2	Second MISFET region
	76-3	Third MISFET region
	77, 77-1 ... 77-m, 80	Cascode MISFET
15	91	First bias current changing switch
	92	Second bias current changing switch
	95, 95a, 95b, 99	Dummy current distribution MISFET
	96, 96a, 96b,	Dummy bias current changing switch
	97, 97a, 97b, 100, 101	Dummy bias current changing switch
20	105	Second current input MISFET

[Name of the Document] Abstract

[Abstract]


[Purpose] To provide a current driving device in which display distortion such as display nonuniformity and the like can be suppressed when the current driving device is
5 used in a display device.

[Solution] A current driving device includes a reference current source **58**, a first MISFET **53** connected to the reference current source **58**, a plurality of current distribution MISFETs **55** which constitutes a current mirror together with the first MISFET **53** and distributes a reference current, a current input MISFET **57** connected to the current
10 distribution MISFETs **55**, and a plurality of current supply sections **59** each of which includes MISFETs constituting a current mirror circuit together with the current input MISFET **57** and supplies a driving current for a pixel circuit. With the plurality of current distribution MISFETs **55** provided, change in gate potential of MISFETs in the current supply section **59** can be suppressed, so that the generation of a crosstalk in a display
15 device can be suppressed.

[Selected Figure] FIG. 4


【書類名】 図面 [Name of The Document] DRAWINGS

【図1】 [FIG.7]




The diagram shows a multi-bit digital-to-analog converter (20) and its feedback loop (40). The converter (20) consists of several stages, each receiving a digital input bit (1, 2, 3, 10, 12, 43) and a common BIAS signal. Each stage uses a differential pair of transistors (e.g., 1, 2; 10, 12; 43, 45) to generate an analog output. The outputs of these stages are summed to produce the final output signal (out). The feedback loop (40) includes a summing junction (3) that combines the output signal with a feedback signal from the output of the converter (4). This combined signal is then fed back into the input of the converter (40) to correct for any errors.


【図3】 [FIG.3]




【図4】 [FIG. 4]



【図5】 [F(9.5)]




【図6】 [F(6.6)]





【図7】


[FIG.7]




【図8】 [F(9-8)]




【図9】 [Figs. 9]



【図10】 [FIG.10]




【図11】 [FIG. 11]




【図12】


[FIG. 12]




【図13】 CFIG.13】




【図14】 [FIG. 14]




【図15】 [FIG. 15]



【図16】 [FIG. 16]




【図17】 [F19.17]




【図18】


[FIG. 18]




【図19】 [FIG. 19]




【図20】 (FIG. 20)



【図 2 1】



【図 22】₅ [FIG. 22]



【図23】 (Figs. 23)

